

## HYDROTAP G5 BHA CELSIUS ARC CHROME



BOILING

FILTERED



HOT & AMBIENT

UNFILTERED



### Order Code H58786Z00AU

Zip HydroTap Design Range CELSIUS Boiling Filtered water, plus Hot and Cold washing up water from a single tap. The system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including boiling water safety mode, 3 energy saving modes including ON/OFF timers and 2 hour sleep mode, antimicrobial protection impregnated into key water paths for enhanced hygiene, and 0.2 micron water filtration.

Manufacturing Code H58786Z00AU

Capacity Residential







Tap	Zip HydroTap Design Range CELSIUS ARC Tap (Chrome)
Water Pressure	Min 170kPa - Max 700kPa
Water Connection	1/2" BSP (G1/2)
Water Supply Requirements	Cold and Hot
Water Valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
Power Rating	1.35kW 220-240V 50Hz
Power Supply	1 x 10 Amp socket outlet
Dimensions	W280mm x D313mm x H333mm
Product Approvals	WaterMark, RCM
Wels Rating	5 Star, 5.5 litres
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

# Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a Zip Certified service technician, observing national and local regulations.
2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1 metre of the product.
3. Zip HydroTap is air-cooled so discrete cabinetry cut-outs are required for ventilation.
4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
5. If you live in a hard water area, we recommend installation of a scale filtration kit.
6. Installation by Zip Professional Service can be arranged with a phone call or through [www.zipwater.com/book-service-visit](http://www.zipwater.com/book-service-visit)

## Installation Detail

BKL2 HydroTap G5 v1.04 11.23 B, BA

Ventilation requirements <small>Contact your local service provider if ventilation is not suitable</small>		HydroTap Tap options			
<b>Clearance envelope</b> Position the Tap and the Command Centre as close together as possible. 		<b>Celsius Arc Tap</b> 		<b>Celsius Cube Tap</b> 	
 <p>Air outlet louvre (if required) Cut-out in doorwall, towards the top of the cabinet</p> <p>Air inlet cut-out (required) Cut-out in cabinet floor</p>		<b>Tap Positioning</b> Position the Tap to dispense into the sink, allowing clearance for a cup or teapot.  <p>Ø35mm hole for Tap</p> <p>4mm buffer pad air space</p> <p>Clearance Envelope</p> <p>Mains cold water isolation valve (not supplied)</p> <p>Air inlet grille</p> <p>IEC Flex &amp; Plug 230-240V, 50Hz power outlet</p>			
<b>Mains hot water supply installation</b> Hot and cold water supply required  <p>35mm hole in sink/benchtop for mixer tap</p> <p>RED marked braided hose to mixer tap</p> <p>Hot water isolation valve (not supplied)</p> <p>BLUE marked braided hose</p> <p>Braided hose to HydroTap Command Centre MAINS inlet</p> <p>Mains water isolation valve (not supplied)</p>					

**HydroTap G5  
B Home, B60**

shown with Celsius Arc Tap

SCALE 1:5  
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.