

**INDUSTRY  
KITCHENS**

www.industrykitchens.com.au 1800 611 058



# HYDROTAP G5 BCHA100 4-IN-1 TOUCH-FREE WAVE TAP WITH CLASSIC MIXER CHROME



**BOILING**



**CHILLED**



**HOT & AMBIENT**

**FILTERED**

**UNFILTERED**

## Order Code H5W624Z00AU

Zip HydroTap Touch-Free Wave 4 in 1 Boiling, Chilled, Filtered water plus Hot and Cold washing up water from two separate taps. The system uses smart infrared 100% touch-free operation that is activated with the Wave of a hand. The water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including boiling water safety mode, 2 energy saving modes including ON/OFF timers and 2 hour sleep mode, 'Quiet' mode with automated intelligent fan speed adjustment, antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology and 0.2 micron water filtration. Easy to install integrated ventilation tray included.



Manufacturing Code	H5W624Z00AU
Capacity	Commercial
Number of people	61-100
Boiling Cups per hour	240
Chilled Cups per hour	175

---

<b>Tap</b>	Zip HydroTap Touch-Free Wave tap (Chrome)
<b>Water Pressure</b>	Min 300kPa - Max 700kPa
<b>Water Connection</b>	1/2" BSP (G1/2)
<b>Water Supply Requirements</b>	Cold
<b>Water Valves</b>	Integrated 500kPa Pressure limiting valve and Dual Check Valve
<b>Power Rating</b>	2.1kW 220-240V 50Hz
<b>Booster Power Rating</b>	Zip HydroTap Booster 2.2kW 220-240V 50/60Hz
<b>Power Supply</b>	2 x 10 Amp socket outlets
<b>Dimensions</b>	W395mm x D464mm x H333mm
<b>Product Approvals</b>	WaterMark, RCM, ARC
<b>Wels Rating</b>	6 Star, 3.0 litres
<b>Warranty</b>	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

---

## Installation Requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
  2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1 metre of the product.
  3. Discrete cabinetry cut-outs are required for ventilation.
  4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
  5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
  6. Installation by Zip Professional Service can be arranged with a phone call or through [www.zipwater.com/book-service-visit](http://www.zipwater.com/book-service-visit)
- 

### Installation Detail

EKL2 HydroTap G5 v1 01 03 21 BC40 BC60



### Ventilation requirements

Contact your local service provider if ventilation is not suitable

#### Clearance envelope

Position the Tap and the Command Centre as close together as possible.

### HydroTap Tap options

Classic Plus

Classic

Elite Plus

Touch-Free Wave

100mm clearance envelope required. For Sink installations, install on the left-hand side of the Sink for ease of access to Boiling water function.

### Mixer Tap options

#### Arc Mixer Tap

35mm hole on sink or benchtop

#### Cube Mixer Tap

35mm hole on sink or benchtop

#### Classic Mixer Tap

35mm hole on sink or benchtop

#### Accessible Mixer Tap

35mm hole on sink or benchtop

### Tap Positioning

Position the Tap to dispense into the sink, allowing clearance for a cup or teapot. Alternatively, mount the HydroTap Tap on a Font (available as an accessory).

35mm hole for HydroTap Tap      35mm hole for Mixer Tap

### Vent tray (kit no. 93540)

### Ventilation details

Detail A. Air inlet grille Cut-out in cabinet floor

Detail B. Vent Tray air outlet Cut-out in cabinet floor

### Clearance Envelope (Detailed)

### Vented mixer tap installation

Only cold water supply required

## HydroTap G5 BC40 H, BC60 H, BC100 H

shown with "Classic Plus" Tap  
and Arc Mixer Tap (V)

SCALE: 1:5  
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.