

INDUSTRY KITCHENS

www.industrykitchens.com.au 1800 611 058



HydroTap G5 BC20 Classic Chrome

Boiling Chilled



Finish: Chrome

Product code: H51702Z00AU

Capacity: Commercial

Zip HydroTap Boiling, Chilled, Filtered water tap features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including 2 boiling water safety modes, 3 energy saving modes including ON/OFF timers and sensor activated 'sleep when it's dark', 'Quiet' mode with automated intelligent fan speed adjustment, antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, and 0.2 micron water filtration.

Specifications

Product name	HydroTap G5 BC20 Classic Chrome
Product code	H51702Z00AU
Filtered water type	BC
Product approvals	WaterMark, RCM, ARC
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

Capacity, weight & dimensions

Number of people	1-20
Boiling cups per hour	100
Chilled cups per hour	75

Plumbing

Water supply requirements	Cold
Water connection	1/2" BSP (G1/2)
Water valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
Water pressure	Min 170kPa - Max 700kPa

Electrical

Power rating	1.9kW 220-240V 50Hz
Power supply	1 × 10 Amp socket outlet

Tap design

Tap	Zip HydroTap CLASSIC Tap (Chrome)
HydroTap style	Classic
Finish	Chrome
Disability options	no

Command centre

Dimensions

W280mm x D478mm x H333mm

Installation

Installation requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.
3. **Discrete cabinetry cut outs are required for airflow. 40mm minimum clearance on cupboard base overhang required otherwise alternative installation options are available.**
4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com/book-service-visit

Files

Installation Layout 3D (DWG)

8K12 HydroTap GS v1.2 01.2025 BC BC20

Ventilation requirements

Contact your local service provider if ventilation is not suitable

Option 1. Cupboard with 40mm min overhang

Option 2. Cupboard with less than 40mm overhang

HydroTap Tap options

Classic Plus
Dimensions: 116mm (width), 216mm (height), 126mm (spout height), Ø46mm (spout diameter). Requires Ø35mm hole.

Classic
Dimensions: 116mm (width), 208mm (height), 126mm (spout height), Ø46mm (spout diameter). Requires Ø35mm hole.

Elite Plus
Dimensions: 112mm (width), 221mm (height), 134mm (spout height), Ø46mm (spout diameter). Requires Ø35mm hole.

Touch-Free Wave
100mm clearance envelope is required.
For Sink installations, install on the left-hand side of the sink for ease of access to Boiling water function.
Dimensions: 116mm (width), 214mm (height), 126mm (spout height), Ø46mm (spout diameter). Requires Ø35mm hole.

Font options

Raised Font with 135mm Extension part no. 95258
Dimensions: 116mm (width), 260mm (height), 351mm (total height), Ø46mm (spout diameter), 116mm (base width), 268mm (base width).

Font with 135mm Extension part no. 90915
Dimensions: 116mm (width), 260mm (height), 351mm (total height), Ø46mm (spout diameter), 104mm (base width), Ø219mm (base diameter).

Cutting detail

Left side: Ø10 for M6 stud, Ø86 hole for bowl, Ø35 hole for tap. Dimensions: 164mm (width), 152mm (height).

Right side: Ø108 hole for bowl, Ø35 hole for tap, Ø10 for M6 stud. Dimensions: 60mm (width), 104mm (width), Ø219mm (diameter).

Tap Positioning

Position the Tap to dispense into the sink. Alternatively, mount on a Font, available as an accessory.

Classic Plus tap
Raised Font with Extension (optional accessory)

Clearance Envelope

4mm buffer pad air space

Mains cold water isolation valve (not supplied)
IEC Flex & Plug 230-240V, 50Hz power outlet
Air inlet grille

200 min.
333
280
50 min.
478

HydroTap G5 BC20
shown with Classic Plus tap and Raised Font (optional accessory)

SCALE 1:5
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.

Installation Layout (PDF)

BIM files



↓ ArchiCAD Swift
Globals Library
(LCF)



↓ ArchiCAD Zip Water
Library (LCF)



↓ BIM downloads



↓ Revit Project File
(RFA)



↓ Revit Virtual
Showroom (RVT)

↓ Download all

Certifications



Environment
ISO 14001



Health & Safety
AS/NZS 4801



Quality
ISO 9001



↓ ARC (PDF)



↓ Environment ISO
(PDF)



↓ Environmental
Product Declaration
Brochure (PDF)



↓ Filter performance
(PDF)



↓ Health & Safety
(PDF)



↓ HydroTap Clean
SDS (PDF)



↓ Quality ISO (PDF)

Manuals & brochures




 Brochure (PDF)



 Instruction manual (PDF)




 Quick guide (PDF)



 Tap operation label (PDF)



 User manual (PDF)

 Download all