




## HydroTap G5 BC20 Classic Plus Chrome

Boiling Chilled

 **Finish:** Chrome

**Product code:** H55702Z00AU

**Capacity:** Commercial

Zip HydroTap Classic Plus Boiling, Chilled, Filtered water tap features simple, intuitive controls including continuous flow to fill bottles, Boiling water safety lock, and antimicrobial protection impregnated within the new Classic Plus touch-pad for enhanced hygiene. The water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including 2 boiling water safety modes, 3 energy saving modes including ON/OFF timers and sensor activated 'sleep when it's dark', 'Quiet' mode with automated intelligent fan speed adjustment, antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, and 0.2 micron water filtration.

# Specifications

Product name	HydroTap G5 BC20 Classic Plus Chrome
Product code	H55702Z00AU
Filtered water type	BC
Product approvals	WaterMark, RCM, ARC
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

# Capacity, weight & dimensions

Number of people	1-20
Boiling cups per hour	100
Chilled cups per hour	75

# Plumbing

Water supply requirements	Cold
Water connection	1/2" BSP (G1/2)
Water valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
Water pressure	Min 170kPa - Max 700kPa

# Electrical

Power rating	1.9kW 220-240V 50Hz
Power supply	1 × 10 Amp socket outlet

# Tap design

Tap	Zip HydroTap CLASSIC PLUS Tap (Chrome)
HydroTap style	Classic Plus
Finish	Chrome

# Command centre

Dimensions

W280mm x D478mm x H333mm

## Installation

### Installation requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.
3. **Discrete cabinetry cut outs are required for airflow. 40mm minimum clearance on cupboard base overhang required otherwise alternative installation options are available.**
4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
6. Installation by Zip Professional Service can be arranged with a phone call or through [www.zipwater.com/book-service-visit](http://www.zipwater.com/book-service-visit)

### Files

Installation Layout 3D (DWG)

8K12 HydroTap GS v1.2 01.2025 BC BC20

#### Ventilation requirements

Contact your local service provider if ventilation is not suitable

**Option 1. Cupboard with 40mm min overhang**

**Option 2. Cupboard with less than 40mm overhang**

#### HydroTap Tap options

**Classic Plus**  
Dimensions: 116mm width, 216mm height, 126mm depth, Ø46mm hole. Requires Ø35mm hole.

**Classic**  
Dimensions: 116mm width, 208mm height, 126mm depth, Ø46mm hole. Requires Ø35mm hole.

**Elite Plus**  
Dimensions: 112mm width, 221mm height, 134mm depth, Ø46mm hole. Requires Ø35mm hole.

**Touch-Free Wave**  
100mm clearance envelope is required.  
For Sink installations, install on the left-hand side of the sink for ease of access to Boiling water function.  
Dimensions: 116mm width, 214mm height, 126mm depth, Ø46mm hole. Requires Ø35mm hole.

#### Font options

**Raised Font with 135mm Extension** part no. 95258  
Dimensions: 116mm width, 260mm height, 200mm depth, Ø46mm hole. Requires Ø35mm hole.

**Font with 135mm Extension** part no. 90915  
Dimensions: 116mm width, 260mm height, 104mm depth, Ø46mm hole. Requires Ø35mm hole.

#### Font options (continued)

**Clearance Envelope**  
A minimum overhang or kickboard height is required for ventilation. Refer to the installation instructions.

**Cutting detail**  
Left: Ø10 for M6 stud, Ø86 hole for bowl, Ø35 hole for tap, 116mm width, 152mm height, 164mm depth.  
Right: Ø108 hole for bowl, Ø35 hole for tap, Ø10 for M6 stud, 60mm width, 104mm depth, Ø219mm diameter.

#### Tap Positioning

Position the Tap to dispense into the sink. Alternatively, mount on a Font, available as an accessory.

Classic Plus tap  
Raised Font with Extension (optional accessory)

4mm buffer pad air space

Clearance Envelope

Mains cold water isolation valve (not supplied)  
IEC Flex & Plug 230-240V, 50Hz power outlet  
Air inlet grille

280mm, 50mm, 478mm

SCALE 1:5  
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.

### HydroTap G5 BC20

shown with Classic Plus tap and Raised Font (optional accessory)

Installation Layout (PDF)

# BIM files



↓ ArchiCAD Swift  
Globals Library  
(LCF)



↓ ArchiCAD Zip Water  
Library (LCF)



↓ Revit Project File  
(RFA)



↓ Revit Virtual  
Showroom (RVT)

↓ Download all

# Certifications



Environment  
ISO 14001



Health & Safety  
AS/NZS 4801



Quality  
ISO 9001



↓ ARC (PDF)



↓ Environment ISO  
(PDF)



↓ Environmental  
Product Declaration  
Brochure (PDF)



↓ Filter performance  
(PDF)



↓ Health & Safety  
(PDF)



↓ HydroTap Clean  
SDS (PDF)



↓ Quality ISO (PDF)

# Manuals & brochures



 Brochure (PDF)



 Instruction manual (PDF)



 Quick guide (PDF)



 Tap operation label (PDF)



 User manual (PDF)

 Download all