



HydroTap G5 BC100 Elite Plus Chrome

Boiling Chilled

 **Finish:** Chrome

Product code: H5E705Z00AU

Capacity: Commercial

Zip HydroTap Design Range Boiling, Chilled, Filtered water tap features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including boiling water safety mode, 2 energy saving modes including ON/OFF timers and 2 hour sleep mode, 'Quiet' mode with automated intelligent fan speed adjustment, antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, and 0.2 micron water filtration.

Specifications

Product name	HydroTap G5 BC100 Elite Plus Chrome
Product code	H5E705Z00AU
Filtered water type	BC
Product approvals	WaterMark, RCM, ARC
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

Capacity, weight & dimensions

Number of people	61-100
Boiling cups per hour	240
Chilled cups per hour	175

Plumbing

Water supply requirements	Cold
Water connection	1/2" BSP (G1/2)
Water valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
Water pressure	Min 250kPa - Max 700kPa

Electrical

Power rating	2.1kW 220-240V 50Hz
Power supply	2 × 10 Amp socket outlets
Booster power rating	Zip HydroTap Booster 2.2kW 220-240V 50/60Hz

Tap design

Tap	Zip HydroTap Design Range ELITE PLUS Tap (Chrome)
HydroTap style	Elite Plus
Finish	Chrome

Command centre

Dimensions

W395mm x D487mm x H333mm

Installation

Installation requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.
3. **Discrete cabinetry cut outs are required for airflow. 40mm minimum clearance on cupboard base overhang required otherwise alternative installation options are available.**
4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com/book-service-visit

Files

Installation Layout 3D (DWG)

Installation Layout 3D (DWG)

Installation Layout (PDF)

Ventilation requirements Contact your local service provider if ventilation is not suitable

Option 1. Cupboard with 40mm min overhang

- 40mm min clearance beside inlet
- 50mm min clearance beside inlet
- 100mm min clearance
- Air inlet grille cut-out (min. 40mm, 325mm)
- Air exhaust cut-out (min. 40mm, 350mm)

Option 2. Cupboard with less than 40mm overhang

- 50mm min clearance beside inlet
- Floor mounting plate cut-out (40mm, 350mm)
- Air exhaust cut-out (60mm, 285mm)

Tap Positioning

Position the Tap to dispense into the sink. Alternatively, mount on a Font, available as an accessory.

- Classic Plus tap
- Raised Font with Extension (optional accessory)
- 4mm buffer pad air space

HydroTap Tap options

- Classic Plus**: 116mm, 216mm, 126mm, Ø46mm, Ø35mm hole required
- Classic**: 116mm, 208mm, 126mm, Ø46mm, Ø35mm hole required
- Elite Plus**: 112mm, 221mm, 134mm, Ø46mm, Ø35mm hole required
- Touch-Free Wave**: 116mm, 214mm, 126mm, Ø46mm, Ø35mm hole required. 100mm clearance envelope is required.

Font options

- Raised Font with 135mm Extension** part no. 95258: 116mm, 260mm, 351mm, Ø46mm, 116mm, 200mm
- Font with 135mm Extension** part no. 90915: 116mm, 260mm, 351mm, Ø46mm, 104mm, Ø219mm

Cutting detail

- Ø10 for M6 stud, Ø86 hole for bowl, Ø35 hole for tap, 116mm, 164mm, 152mm
- Ø108 hole for bowl, Ø35 hole for tap, Ø10 for M6 stud, 60mm, 104mm, Ø219mm

Wiring Diagram

- Booster: Note: The 500mm braided hoses supplied cannot be lengthened
- IEC Flex & Plug 230-240V, 50Hz power outlet
- Clearance Envelope
- Air inlet grille
- Mains cold water isolation valve (not supplied)
- Dimensions: 200mm min., 333mm, 50mm min., 395mm, 487mm

HydroTap G5 BC100

shown with Classic Plus tap and Raised Font (optional accessory)

SCALE 1:5
ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.

BIM files



↓ ArchiCAD Swift
Globals Library
(LCF)



↓ ArchiCAD Zip Water
Library (LCF)



↓ Revit Project File
(RFA)



↓ Revit Virtual
Showroom (RVT)

↓ Download all

Certifications



Environment
ISO 14001



Health & Safety
AS/NZS 4801



Quality
ISO 9001



↓ ARC (PDF)



↓ Environment ISO
(PDF)



↓ Environmental
Product Declaration
Brochure (PDF)



↓ Filter performance
(PDF)



↓ Health & Safety
(PDF)



↓ HydroTap Clean
SDS (PDF)



↓ Quality ISO (PDF)

Manuals & brochures



 Brochure (PDF)



 Instruction manual (PDF)



 Quick guide (PDF)



 Tap operation label (PDF)



 User manual (PDF)

 Download all