ADANDE SIDE ENGINE UNIT (VCS)




Applications


- Meat and fish prep & storage
- Deli and larder prep & storage
- Pastry and pasta prep & storage
- Dessert prep & storage
- Point of use storage
- Frozen storage by the deep fryer
- Mise en Place prep & garnish storage

Operational Benefits

- Reliable: amazing temperature stability
- Green: extremely energy efficient
- Cuts food wastage
 - Food does not dehydrate
 - No condensation on the food
- Ergonomically efficient
- Minimal maintenance costs
- Quick and easy to clean
- Robust and reliable









DIMENSIONS - VCS1.CT - Elevation & Plan View

Storage Capacity Per Drawer 4 x 1/1 GN Pans 100 mm Deep or equivalent





TOP & BASE OPTIONS - Worktops and Castors

(HS) - protects unit tops exposed to temperatures up to 200°C	High Castors				$\overline{\bigcirc}$	
The non load bearing			Standard Castors		Locking Roller Base	
Finished Height & Load Bearing Weight with Heat Shield Top (HS)	624mm	VCS1.HCHS	545mm	VCS1.CHS	500mm	VCS1.RHS
	235 kg		300 kg		285 kg	
Finished Height & Load Bearing Weight with Worktop (W)	n/a		502mm	VCS1.CW	458mm	VCS1.RW
	n/a		300 kg		300 kg	

CLIMATE TESTING: Tested to Climate Class 4 (30°C and 55% relative humidity) for temperature and energy consumption. Tested to Climate Class 5 (40°C and 40% relative humidity) for temperature MAINS: 230 Vac 50 Hz also 60 Hz available. (BC): Blast Chiller Option available.

Imported and distributed exclusively by:

Tom Stoddart Pty Ltd 39 Forest Way, Karawatha, QLD 4117 1300 79 1954 www.stoddart.com.au adande@stoddart.com.au

