



Fagor Kore 700 Bench Top Chrome Electric Griddle NG FT-E710CL

Quick Overview



- Deep-drawn surface tops manufactured in 1.5 mm thick AISI-304 stainless steel
- Laser-cut joints, automatic welding, and polishing. Hidden screws
- 12 or 15-mm thick mild steel fry tops which are quick-heating and high power
- Whole-module fry tops have two separate heating areas
- Rapid reaction and recovery times of the fry-top temperature
- The fry tops are welded to the deep-drawn surface top
- The deep-drawn shell and its rounded edges and corners make cleaning much easier
- The fry top is tilted towards the front to make it easier to collect grease and liquids
- Fitted with an opening to collect cooking grease and a tray to store it which can store up to 2 liters depending on the model
- Optional anti-splash side and rear guards, easy to remove
- High-temperature enameled cast iron flue protector
- Access to components from the front
- Machines with IPX5 grade water protection
- Electrically heated models with stainless steel heating elements; thermostatic temperature control, between 100 and 300° C.
- Safety thermostat
- Model with smooth plate of 328 x 468mm
- Single heating zone
- Optional stands available

Description

Fagor Kore 700 Bench Top Chrome Electric Griddle NG FT-E710CL

Key Features

- Deep-drawn surface tops manufactured in 1.5 mm thick AISI-304 stainless steel
- Laser-cut joints, automatic welding, and polishing. Hidden screws
- 12 or 15-mm thick mild steel fry tops which are quick-heating and high power
- Whole-module fry tops have two separate heating areas
- Rapid reaction and recovery times of the fry-top temperature
- The fry tops are welded to the deep-drawn surface top
- The deep-drawn shell and its rounded edges and corners make cleaning much easier
- The fry top is tilted towards the front to make it easier to collect grease and liquids
- Fitted with an opening to collect cooking grease and a tray to store it which can store up to 2 liters depending on the model
- Optional anti-splash side and rear guards, easy to remove
- High-temperature enameled cast iron flue protector
- Access to components from the front
- Machines with IPX5 grade water protection
- Electrically heated models with stainless steel heating elements; thermostatic temperature control, between 100 and 300 ° C.
- Safety thermostat
- Model with smooth plate of 328 x 468mm
- Single heating zone
- Optional stands available

2 Years Parts & Labour Plus 2 Years Parts Only Warranty When Products Registered Within 14 Days Of Invoice

Your Shipping Specifications

Net Weight (Kg)	137
Width (mm)	800
Depth (mm)	730
Height (mm)	290
Packing Width (mm)	822
Packing Depth (mm)	840
Packing Height (mm)	535
Power	415V, 10kW/3-N
Warranty	2 Years Parts & Labour Plus 2 Years Parts Only Warranty When Products Registered Within 14 Days Of Invoice