



CR.BB.U.AG.RC.3

Back Bar Refrigerators Refrigerated

Horizontal



Product Code:

- CR = Culinaire Refrigerated
- BB = Back Bar
- U = Under Bench
- AG = Aluminium Framed Glass
- RC = Remote Service Compartment
- 3 = 3 Door

Optional Extras:

Frameless Glass Doors

- Add FG to code CR.BB.U.FG.RC.3

Stainless Steel Framed Glass Doors, Continuous Folded Handle

- Add SG to code CR.BB.U.SG.RC.3

Stainless Steel Framed Glass Doors, Recessed Handle

- Add SGR to code CR.BB.U.SGR.RC.3

Equipment Legs

- Add EL to code CR.BB.U.AG.RC.EL.3
- Factory fitted

(If Required, must be nominated at time of order)

Left Hand Services

Remote Service Compartment

- Add L to code CR.BB.U.AG.RCL.3

Self Contained

Self Contained Right Hand

- Add SC to code CR.BB.U.AG.SC.3

Self Contained Left Hand

- Add SCL to code CR.BB.U.AG.SCL.3

Technical Data:


- Dimensions: W x D x H: 1970 x 700 x 960
- * Remote Refrigeration Load: 1250 watts at -10°C SST
- Refrigerant Type: R507 or 404A
- Pipe Connection Inlet: 1/2"
- Pipe Connection Outlet: 1/4"
- Total Connected Load: 0.6kW
- Electrical Connection: 240V 1Ø + N + E

Note: Refrigeration load is calculated at the cabinet


Due to continuous product research and development, the information contained herein is subject to change without notice

Product Information:


- Keeps contents at a cool +1°C to +4°C in 32°C ambient temperature
 - Air blown from rear to front over a full length cross fin coil to ensure maximum recovery and even temperature in the busiest environments
 - High impact, low energy L.E.D. lighting ensures maximum product visibility
 - Aluminum framed low energy double glazed, heated and toughened glass doors are self-closing and self-sealing to ensure ease of operation & improved efficiency (as standard)
 - Serviceable heater wire in cabinet fascia to prevent condensation
 - Choice of either stainless steel or black internal and external finishes (as standard)
 - All doors are left hand hinged with hold open stays, as standard. Contact your local sales rep for other door configurations
 - The refrigerator is plinth mounted as standard. 150mm equipment legs available as an optional extra, must be specified at the time of ordering
 - All services are at the right hand end of the refrigerator as standard. Can be ordered as left hand by adding "L" to code (refer left hand services)
 - Supplied with 4 adjustable shelves per door
 - Available in 2-7 doors
 - Supplied with a remote service compartment for connection to a remote condenser unit to be supplied separately and connected by a qualified refrigeration contractor and electrician
 - Condensate is to be plumbed to waste
- Self Contained Refrigerators** (contact your Stoddart representative)
- Self contained refrigerators are available in 2-4 doors
 - Condensate is to be plumbed to waste



Plan View



Front Elevation



End Elevation



Proudly Manufactured in Australia

Manufactured By:

Tom Stoddart Pty Ltd. ABN 16 009690251
 39 Forest Way, Karawatha 4117 Queensland Australia
 Tel : +61 7 3440 7600 Fax : +61 7 33441000
 Web site: www.stoddart.com.au

