

Technical Data Sheet

CR.RPR.SC.1175

Roll-In Plating Refrigerator Refrigerated Suits 2 x 1/1 Gastronorm Trolleys

Product Code:

- CR= Culinaire RefrigeratedRPR= Roll-In PlatingDefine refuse
- SC 1175
- Refrigerator = Self Contained
- = 1175mm Wide

CR.RPR.SC.L.1175

Left Hand Drain & Left Hand Hinged Door

- Add L to code

Accessories

1/1 GN Trolley - Simply Stainless


- Supplied flat packed SS16.1/1 ready for assembly

Technical Data:


Dimensions: W x D x H: Total Connected Load: Electrical Connection: 1175 x 1177 x 2360 2.4kW 240V 1Ø + N + E




- Keeps contents at a cool +2°C to +4°C in 20°C controlled environment
- The combination of an air curtain and fan forced refrigeration from the top, back and each side creates a uniform temperature within the refrigerator
- The door at the foot of the refrigerator assists with maintaining the internal temperature by minimising the loss of refrigerated air while still allowing a trolley to be rolled in and out and loaded without constantly opening the door
- For extended holding periods, a roller curtain is provided which magnetically seals opening opening to the top of the door
- Heater wire in cabinet fascia to prevent condensation
- L.E.D. lighting provides illumination to the interior
- Robust stainless steel construction
- · Fitted with roll-in roll-out to base of refrigerator
- Suits either a double 1/1 gastronorm trolley or 2 x 1/1 gastronorm trolleys (sold separately)
- Condensate drain is located on right hand side of the refrigerator as standard. Additionally the door to the foot of the refrigerator is right hand hinged as standard.
- The refrigerator an be ordered with left hand drain and hinged door by adding ".L" to code
- Condensate is to be plumbed to waste



Plan View





End Elevation



Due to continuous product research and development, the information contained herein is subject to change without notice



Tom Stoddart Pty Ltd. ABN 16 009690251 39 Forest Way, Karawatha 4117 Queensland Australia Tel : +61 7 3440 7600 Fax : +61 7 33441000 Web site: www.stoddart.com.au STODDART