



PUMP KITS

NEW!

with even more powerful barrel pump motor FEM 4070



Innovators
in Flow Technology

DRUM AND CONTAINER PUMPS





FLUX Pump Kits for:

Acids and alkalis	4 – 5
Concentrated acids and "AdBlue®"	6
Petroleum products	7
Flammable liquids	8
Universal applications	9
99,98 % barrel emptying	10
The great range of FLUX pumps	11

FLUX Pump Kits include everything for immediate operation.

They consist of :

- Motor
- Pump
- Hose
- Quick action tap
- Compression gland

No longer do you have the tedious chore of leafing through catalogues for numerous items, they are all contained in the FLUX Pump Kit. Select the most suitable combination and see the advantages of buying a FLUX Pump Kit, the all-inclusive service!

FLUX PUMP KIT "JUNIORFLUX"

For filling, emptying, transferring or dispensing acids and alkalis, such as battery acid, ammonia water, glycol, caustic soda and soapy water.

Delivery rate max. 40 l/min, delivery head max. 5,2 m.*

When using the pump with a discharge hose and a hand tap, the delivery rate will be approx. 15 l/min.

Viscosity max. 250 mPas (cp), temperature max. 45 °C.

JUNIORFLUX F 314 PP-25/19 in Polypropylene

sealless, shaft in Hastelloy C, impellor in ETFE, outer-Ø 25 mm, thread on outlet G 1 A (BSP 1" male)

Commutator motor 230 Volt, 50 Hz, 230 Watt, IP 24, with two-speed switch for smooth emptying

with 5 m power supply cable and 2-pole plug

Accessories:

Hose connection PP, 1,5 m flexible PVC hose DN 13, 2 hose clips, quick action tap PP, seal FKM

Part No./Weight

Immersion length 700 mm **314 43 007/2,4 kg**



For transferring acids like boric acid, fruit acids, phosphoric acid, hydrochloric acid and sulphuric acid (at 80%).

Delivery rate max. 47 l/min, delivery head max. 6,8 m.*

When using the pump with a discharge hose and a hand tap, the delivery rate will be approx. 30 l/min.

Viscosity max. 250 mPas (cp), temperature max. 45 °C.

JUNIORFLUX F 310 PP-32/25 in Polypropylene

with mechanical seal in ceramic oxide, PTFE/carbon, seal FKM, shaft in Hastelloy C, impellor in ETFE, outer-Ø 32 mm, thread on outlet G 1 A (BSP 1" male)

Commutator motor 230 Volt, 50 Hz, 230 Watt, IP 24 with two-speed switch for smooth emptying

with 5 m power supply cable and 2-pole plug

Accessories:

Hose connection PP, 1,5 m flexible PVC hose DN 19, 2 hose clips, quick action tap PP, seal FKM

Part No./Weight

Immersion length 1000 mm **310 43 010/2,7 kg**



*Maximum performance data obtained with water (20 °C) at the outlet connection of the pump, without discharge hose and hand tap.

FLUX PUMP KIT "ACIDS"



For transferring acids like boric acid, fruit acids, phosphoric acid, hydrochloric acid and sulphuric acid (at 80%).

Delivery rate max. 165 l/min, delivery head max. 9,5 m.*

When using the pump with a discharge hose and a hand tap, the delivery rate will be approx. 40 l/min.

Viscosity max. 600 mPas (cp), temperature max. 50 °C.

Barrel pump F 430 PP-40/33 in Polypropylene

with mechanical seal in ceramic oxide, PTFE/carbon, seal in FKM, shaft in Hastelloy C, impellor in ETFE, outer-Ø 40 mm, thread on outlet G 1 1/4 A (BSP 1 1/4" male)

Commutator motor FEM 4070, 230 Volt, 50 Hz, 500 Watt, IP 24, with speed-range adjustment and no-volt release

with 5 m power supply cable and 2-pole plug

Accessories:

Hose connection PP, 2 m flexible PVC hose DN 19, 2 hose clips, quick action tap PP, seal FKM, FLUX-Clip, compression gland PP conductive (G 2)

Part No./Weight

Immersion length 1000 mm	407 40 010/5,1 kg
Immersion length 1200 mm	407 40 012/5,3 kg

New!



New!

FLUX PUMP KIT "ALKALIS"

For transferring alkalis and acids like caustic potash, caustic soda, ammonia water, formic acid (at 50%) and acetic acid (at 80%).

Delivery rate max. 165 l/min, delivery head max. 9,5 m.*

When using the pump with a discharge hose and a hand tap, the delivery rate will be approx. 40 l/min.

Viscosity max. 600 mPas (cp), temperature max. 50 °C.

Barrel pump F 424 PP-41/36 in Polypropylene

sealless, shaft in Hastelloy C, impellor in ETFE, outer-Ø 40 mm, foot piece Ø 41mm, thread on outlet G 1 1/4 A (BSP 1 1/4" male)

Commutator motor FEM 4070, 230 Volt, 50 Hz, 500 Watt, IP 24, with speed-range adjustment and no-volt release

with 5 m power supply cable and 2-pole plug

Accessories:

Hose connection PP, 2 m PVC hose DN 19, 2 hose clips, quick action tap PP, seal EPDM, FLUX-Clip, compression gland PP conductive (G 2)

Part No./Weight

Immersion length 1000 mm	407 44 010/5,1 kg
Immersion length 1200 mm	407 44 012/5,3 kg

New!

New!



FLUX PUMP KIT "CONCENTRATED ACIDS"

For transferring concentrated acids like hydrobromic acid, chromic acid, chloric acid, hydrofluoric acid, nitric acid, sulphuric acid and sodium hypochlorate.

Delivery rate max. 170 l/min, delivery head max. 9,5 m.*

When using the pump with a discharge hose and a hand tap, the delivery rate will be approx. 40 l/min.

Viscosity max. 600 mPas (cp), temperature max. 100 °C.

Barrel pump F 430 PVDF-40/33 in Polyvinylidenfluoride

with mechanical seal in ceramic oxide, PTFE/carbon, seal in FKM, shaft in Hastelloy C, impellor in ETFE, outer-Ø 40 mm, thread on outlet G 1 1/4 A (BSP 1 1/4" male)

Commutator motor F 458, 230 Volt, 50 Hz, 460 Watt, IP 55, with no-volt release

with special corrosion-resistant painting, 5 m power supply cable and safety plug

Accessories:

Hose connection PVDF, 2 m chemical hose DN 19, 2 hose clips, quick action tap PVDF, seal FKM, FLUX-Clip, compression gland PP conductive

Part No./Weight

Immersion length 1000 mm	458 60 010 /8,9 kg
Immersion length 1200 mm	458 60 012 /9,2 kg



New!



New!

FLUX PUMP KIT "AdBlue®"

For transferring "AdBlue®" out of containers.

Delivery rate max. 85 l/min, delivery head max. 18 m.*

When using the pump with a discharge hose and a hand tap, the delivery rate will be approx. 30 l/min.

Temperature max. 50°C.

Barrel pump F 424 PP/S-41/35Z in Polypropylene

sealless, shaft in stainless steel 316 Ti, impellor in ETFE, outer-Ø 40 mm, foot piece Ø 41 mm, thread on outlet G 1 1/4 A (BSP 1 1/4" male)

Commutator motor FEM 4070, 230 Volt, 50 Hz, 500 Watt, IP 24, with speed-range adjustment and no-volt release

with 5 m power supply cable and 2-pole plug

Accessories:

Hose connection PP, 6 m special hose DN 16, self-locking quick action tap, FLUX-Clip and compression gland PP conductive (G 2)

Part No./Weight

Immersion length 1200 mm	407 41 ZV6 /10,3 kg
--------------------------	----------------------------

*Maximum performance data obtained with water (20 °C) at the outlet connection of the pump, without discharge hose and hand tap.

For transferring petroleum products like diesel oil, fuel oil, hydraulic oil, lube oil and engine oil.

Delivery rate max. 215 l/min, delivery head max. 10 m.*

When using the pump with a discharge hose and a hand tap, the delivery rate will be approx. 65 l/min.

Viscosity max. 600 mPas (cp), temperature max. 80 °C.

Barrel pump F 430 AL-41/38 in Aluminium alloy

with mechanical seal in ceramic oxide, PTFE/carbon, seal NBR, shaft in stainless steel 316 Ti, impellor in ETFE, outer-Ø 41 mm, thread on outlet G 1 1/4 A (BSP 1 1/4" male)

Commutator motor FEM 4070, 230 Volt, 50 Hz, 500 Watt, IP 24, with speed-range adjustment and no-volt release

with 5 m power supply cable and 2-pole plug

Accessories:

Hose connection AL, 2 m petroleum hose DN 25, 2 hose clips, quick action tap AL, seal NBR, FLUX-Clip, compression gland PP conductive

Part No./Weight

Immersion length 1000 mm **407 10 010/6,4 kg**

Immersion length 1200 mm **407 10 012/6,7 kg**

New!



New!

Delivery rate max. 220 l/min, delivery head max. 12 m.*

When using the pump with a discharge hose and a hand tap, the delivery rate will be approx. 80 l/min.

Viscosity max. 800 mPas (cp), temperature max. 80 °C.

Barrel pump and accessories as above, but complete with

Commutator motor F 457, 230 Volt, 50 Hz, 800 Watt, IP 24, with no-volt release

with 5 m power supply cable and 2-pole plug

Part No./Weight

Immersion length 1000 mm **457 10 010/7,8 kg**

Immersion length 1200 mm **457 10 012/8,1 kg**



FLUX PUMP KIT "FLAMMABLE LIQUIDS"

For transferring flammable liquids like acetone, butyl alcohol, ethyl alcohol, methyl alcohol, gasoline, toluene, xylene, etc.

Delivery rate max. 200 l/min, delivery head max. 9,5 m.*

When using the pump with a discharge hose and a hand tap, the delivery rate will be approx. 50 l/min.

Viscosity max. 600 mPas (cp), temperature max. 100 °C.

Barrel pump F 424 S-43/38 in stainless steel tested and certified according to ATEX-Directive 94/9/EC, category 1/2, for use in Zone 0.

sealless, shaft in stainless steel 316 Ti, impellor in ETFE, outer-Ø 41, foot piece Ø 43 mm, thread on outlet G 1 1/4 A (BSP 1 1/4" male)

Commutator motor F 460 Ex, 230 Volt, 50 Hz, 460 Watt, explosion-proof to II 2 G EEx de IIC T6 according to ATEX-Directive 94/9/EC, category 2, with no-volt release

with 5 m power supply cable and safety plug (not explosion-proof)

Accessories:

Earth ground wire 2 m long, universal hose DN 21, 2 m long, electrically conductive, quick action tap MS, seal PTFE, FLUX-Clip, compression gland PP conductive

Part No./Weight

Immersion length 1000 mm	460 24 010/10,9 kg
Immersion length 1200 mm	460 24 012/11,4 kg



Delivery rate max. 240 l/min, delivery head max. 13 m.*

When using the pump with a discharge hose and a hand tap, the delivery rate will be approx. 55 l/min.

Viscosity max. 800 mPas (cp), temperature max. 100 °C.

Barrel pump and accessories as above, but complete with

Compressed air motor F 416 Ex, 470 Watt at 6 bar, explosion-proof to II 2 G cp IIC T6 according to ATEX-Directive 94/9/EC, category 2.

Part No./Weight

Immersion length 1000 mm	416 24 010/7,4 kg
Immersion length 1200 mm	416 24 012/7,9 kg

*Maximum performance data obtained with water (20 °C) at the outlet connection of the pump, without discharge hose and hand tap.

FLUX PUMP KIT "UNIVERSAL APPLICATIONS"



In the following industries: paint, varnish, food, cosmetic and pharmaceutical.

Delivery rate max. 240 l/min, delivery head max. 13 m.*

When using the pump with a discharge hose and a hand tap, the delivery rate will be approx. 50 l/min.

Viscosity max. 800 mPas (cp), temperature max. 100 °C.

Barrel pump F 430 S-41/38 in Stainless steel tested and certified according to ATEX-Directive 94/9/EC, category 1/2, for use in Zone 0.

with mechanical seal in ceramic oxide, PTFE/carbon, seal FKM, shaft in stainless steel 316 Ti, impellor in ETFE, outer-Ø 41 mm, thread on outlet G 1 1/4 A (BSP 1 1/4" male)

Compressed air motor F 416 Ex, 470 Watt at 6 bar, explosion-proof to II 2 G cp IIC T6 according to ATEX-Directive 94/9/EC, category 2.

Accessories:

Earth ground wire 2 m long, universal hose DN 21, 2 m long, complete with fittings in stainless steel on both ends, electrically conductive, quick action tap stainless steel, seal PTFE/FEP, FLUX-Clip, compression gland PP conductive

Part No./Weight

Immersion length 1000 mm	416 20 010/7,6 kg
--------------------------	--------------------------

Immersion length 1200 mm	416 20 012/8,1 kg
--------------------------	--------------------------



Delivery rate max. 200 l/min, delivery head max. 9,5 m.*

When using the pump with a discharge hose and a hand tap, the delivery rate will be approx. 50 l/min.

Viscosity max. 600 mPas (cp), temperature max. 100 °C.

Barrel pump and accessories as above, but complete with

Commutator motor F 460 Ex, 230 Volt, 50 Hz, 460 Watt, explosion-proof to II 2 G EEx de IIC T6 according to ATEX-Directive 94/9/EC, category 2, with no-volt release

with 5 m power supply cable and safety plug (not explosion-proof)

Part No./Weight

Immersion length 1000 mm	460 20 010/11,1 kg
--------------------------	---------------------------

Immersion length 1200 mm	460 20 012/11,6 kg
--------------------------	---------------------------

FLUX PUMP KIT "99,98 % BARREL EMPTYING"

The safe and cost-efficient solution for transferring high value or hazardous liquids.

Delivery rate max. 115 l/min, delivery head max. 8 m.*

When using the pump with a discharge hose and a hand tap, the delivery rate will be approx. 35 l/min.

Viscosity max. 600 mPas (cp), temperature max. 100 °C.

Barrel pump F 425 S-41/34 in Stainless steel tested and certified according to ATEX-Directive 94/9/EC, category 1/2, for use in Zone 0.

with mechanical seal in ceramic oxide, PTFE/carbon, seal FKM, shaft in stainless steel 316 Ti, impellor in ETFE, outer-Ø 41 mm, thread on outlet G 1 1/4 A (BSP 1 1/4" male)

Commutator motor F 460 Ex, 230 Volt, 50 Hz, 460 Watt, explosion-proof to II 2 G EEx de IIC T6 according to ATEX-Directive 94/9/EC, category 2, with no-volt release

with 5 m power supply cable and safety plug (not explosion-proof)

Accessories:

Earth ground wire 2 m long, universal hose DN 21, 2 m long, complete with fittings in stainless steel on both ends, electrically conductive, quick action tap stainless steel, seal PTFE/FEP, FLUX-Clip, compression gland PP conductive

Part No./Weight

Immersion length 1000 mm	460 25 010/11,9 kg
Immersion length 1200 mm	460 25 012/12,4 kg



ACCESSORIES - FLUX LIQUID METERS

If you want to keep your liquids under control, FLUX Pump Kits can be completed by a Liquid Meter Type FMC 100.

3 models are available in PP, ETFE or Stainless steel for flowrates of 10 – 100 l/min.

An easy-to-read 7-digit LCD together with multifunctional keys ensures a simple calibration and input, everything for easy use by the operator.

All models are explosion-proof to II 2 G EEx ia IIB T6 according to ATEX-Directive 94/9/EC.

For detailed information and part numbers please refer to our catalogue FLUX LIQUID METER TYPE FMC, which is available on simple request.



New! Liquid Meter Type FMT 50 PP

Liquid meter with interlocked wheel impeller in the measuring chamber, in conjunction with our JUNIORFLUX pumps.

Construction in PP, not ex-proofed, inlet connection G 1 (BSP 1"), outlet connection G 1A (BSP 1" male).



*Maximum performance data obtained with water (20 °C) at the outlet connection of the pump, without discharge hose and hand tap.



YES!

I am interested in top class pump technology.
Please send the following catalogues:

☐ FLUX JUNIORFLUX

☐ FLUX HIGH VISCOSITY LIQUID PUMPS

☐ FLUX BARREL AND CONTAINER PUMPS

☐ FLUX CENTRIFUGAL IMMERSION PUMPS

☐ FLUX LIQUID METERS

☐ FLUX AIR-OPERATED DIAPHRAGM PUMPS

☐ FLUX MIXERS

Mr / Mrs

Company

Address

Telephone

Fax

e-mail

Please mark with a cross, complete the address and then send us a fax. Fax number see on the back page!



INNOVATORS IN FLOW TECHNOLOGY

All around the globe, FLUX is synonymous with highest standards in pump technology. Whether it is drum and container pumps, high viscosity liquid pumps, vertical centrifugal immersion pumps, air-operated diaphragm pumps, liquid meters, mixers or top class accessories – FLUX with its complete and comprehensive range is always the one to address to. Benefit from our competence. We look forward to hearing from you!

FLUX-GERÄTE GMBH
Talweg 12 · D-75433 Maulbronn
Tel. 07043 101-440 · Fax 07043 101-444
Fax International +49 7043 101-555
info@flux-pumpen.de · www.flux-pumpen.de