Accessories

Productdetail

Specification

Order No.



Trolley for horizontal eccentric screw pump B70H

For mobile use of B70. With fixing material to assemble the motor.

Material: Stainless steel (316Ti)
Dimensions trolley 32.3" x 20.5" x 37"

Trolley 0208-194



PVC hose

Transparent PVC hose for non flammable liquids

Operating pressure: 203 psi

Temperature of liquid: 32 °F up to 149 °F

Nominal diameter: 1 1/2" **0374-469** 2" **0374-470**



Universal chemical hose

Color coding: "blue/white/blue".

Suitable for 95% of all customary industrial chemicals such as almost all acids and alkalis, mineral oil products and solvents of all kinds. Foodstuff conformity of inner layer. Internal finish: Smooth special lining of ultra high molecular polyethylene (U-PE) with spiralled OHM conductive stripes, electrically conductive. External finish: Electrically conductive EPDM. Light grey with OHM conductive stripes, tin-plated steel wire filament (from DN 25).

Type Ω/T smaller than 10⁶ Ohm (acc. to DIN EN 12115:2011).

Operating pressure: max. 232 psi
Temperature of liquid: -22 °F up to 212 °F

Nominal diameter: 1 1/2" **0374-478 • 0374-479 •**

Suitabe for transferring flammable and easy flammable liquids (e.g. Ethanol, petrol) or in explosive hazard area.

Specification Order No. Product detail

Hose clamps

Stainless steel hose clamp to attach hoses/accessories to the pump outlet.

Nominal diameter: 1 1/2" **0000-403** 2" **0000-404**



Hose connection with Tri-clamp

For connecting the hose to the horizontal eccentric screw pump B70H, discharge spout or Tri-Clamp armatures (comprising a hose connection, locking clamp and seal) Material: Stainless steel (1.4404)

 Connection:
 for hose nominal diameter:
 Seal:

 Tri-Clamp DN 50
 DN 38 (1 1/2")
 FPM
 0204-878

 Tri-Clamp DN 50
 DN 50 (2")
 FPM
 0204-880



Please note:

The assembler is responsible for the professional fixing of the hose according to the current Pressure Equipment Directive.

Hose connector with Tri-clamp

For connection of conductive hose onto the horizontal eccentric screw pump B70H, discharge spout or Tri-Clamp armatures in explosive hazardous area. The hose connector ensures a highly conduction transition between conductive hose and pump/armature. The ohmic resistance between the armatures must be lower than 10⁶ Ohm. (Consisting of hose connector, clamp collars, locking clamp and seal) Material: Stainless steel (1.4404)

 Connection:
 for hose Nominal diameter:
 Seal:

 Tri-Clamp DN 50
 DN 50 (2")
 EPDM
 0204-868 ●

 Tri-Clamp DN 50
 DN 50 (2")
 FPM
 0204-869 ●



