

# Fast Pack - Valve/Actuator Packages

**SHIPS IN  
24 HRS !**



## Series 92/Type-57 Butterfly Valve

### Standard Features (Sizes 1-1/2" - 8")

- UL-508 listed electric actuator
- Type-57 PVC body, PP disc, EDPM or FKM seals, wafer style
- 120 VAC capacitor-run reversing type motor
- Thermal overload protection with auto reset
- Declutchable manual override
- Visual beacon position indicator
- 15 second cycle time\* 1-1/2"– 4", 32 second cycle time 6" and 8" Type-57
- Mechanical brake supplied as standard for 6" and 8" Type-57
- Weatherproof enclosure rated Type 4X. Has a thermally bonded powder coat finish with stainless steel trim
- Two end of travel limit switches
- Two additional limit switches for indication
- PPG mounting bracket with 304 stainless steel coupling and hardware, 304 stainless steel mounting bracket, coupling and hardware sizes 6" and 8"
- Complete factory assembled and tested actuated valve package

**SHIPS IN  
24 HRS !**



## Series 92/Type-21 Ball Valve

### Standard Features (Sizes 1/2" - 4")

- UL-508 listed electric actuator
- Type-21 PVC with EPDM or FKM seals, true union ball valve
- Type-21 1/2" – 2" supplied with both socket and threaded ends, 2-1/2"– 4" socket only
- 120 VAC capacitor-run reversing type motor
- Thermal overload protection with auto reset
- Declutchable manual override
- Visual beacon position indicator
- 15 second cycle time\*
- Weatherproof enclosure rated Type 4X. Has a thermally bonded powder coat finish with stainless steel trim
- Two end of travel limit switches
- Two additional limit switches for indication
- PPG mounting bracket with 304 stainless steel coupling and hardware
- Complete factory assembled and tested actuated valve package

Valve Type	Size	Actuation Model	Input Voltage	L.R. Amps	Duty Cycle
Type-21	1/2 - 3	S92M2XW	115 VAC	0.5	100%
Type-21	4	A92M2XW	115 VAC	0.8	75%
Type-57	1-1/2 - 4	S92M2XW	115 VAC	0.5	100%
Type-57	6	B92BRM2XW	115 VAC	0.8	100%
Type-57	8	C92BRM2XW	115 VAC	1.0	50%

\*Cycle times approximate.