

Specifications

General

Operating Range

2839	0.055 to 100 μ S	0.02 to 50 ppm	18.2 M Ω to 10 K Ω
2840	1 to 1,000 μ S	0.5 to 500 ppm	1 M Ω to 1 K Ω
2841	10 to 10,000 μ S	5 to 5,000 ppm	
2842	100 to 200,000 μ S	50 to 100,000 ppm	

Cell Constant Accuracy \pm 2% when the custom cell constant is entered into the transmitter/meter or when wet calibrated with a traceable standard.

Dual-Threaded Process Connection
 -1V versions: 3/4 in. NPT
 -1VD versions: ISO 7/1-R 3/4

Cable Length (use for the 2839, 2840, 2841 and 2842)

Standard	4.6 m (15 ft)
Maximum	30 m (100 ft) all sensors when used with the 9900, 9950 and direct conductivity/resistivity modules

2850 cable length 4.6 m (15 ft) maximum for all cells

Temperature Element Pt1000

Temperature Response, t

0.01 cell	5 sec.
0.10 cell	10 sec.
1.0 cell	20 sec.
10.0 cell	30 sec.

Temperature Accuracy \pm 0.5 $^{\circ}$ C \pm 0.9 $^{\circ}$ F

Wetted Materials

Electrode Material 316 SS

Threaded Process Connection PVDF

Internal O-ring (2841 and 2842) FKM

Insulator Material PVDF

Max. Temperature/Pressure Rating

131 $^{\circ}$ C @ 2.76 bar 268 $^{\circ}$ F @ 40 psi

Storage Temperature -20 $^{\circ}$ C to 131 $^{\circ}$ C -4 $^{\circ}$ F to 268 $^{\circ}$ F

Shipping Weight

2839 0.34 kg 0.74 lb

2840, 2841, 2842 0.30 kg 0.66 lb

Standards and Approvals


RoHS compliant, China RoHS

Manufactured under ISO 9001, ISO 14001 and ISO 45001


Dimensions

Dual-Threaded Electrodes

3-2839-1V(D) (0.01 cell)




3-2840-1V(D) (0.1 cell)




Dual threads 3/4 NPT or ISO 7/1-R 3/4 front and back

3-2841-1V(D) (1.0 cell)*



Dual threads 3/4 NPT or ISO 7/1-R 3/4 front and back

3-2842-1V(D) (10.0 cell)*




* Although these electrodes look similar in design, there is an inherent difference. From the bottom view, the 2841 electrode features a simple plastic insert. However, the 2842 electrode features a complex plastic insert with four holes through which liquid flows.

Integral Mount Sensor






The 2839-2842 Dual Threaded Conductivity Electrodes can form an Integral Mount System with the 3-9900-1 Signet Transmitter when using the 3-9900.396 Direct Conductivity Module, angle adapter and the 8052 Integral Mount Kit.

Complete Integral Mount System with 9900 transmitter are available through our Specials program.



System Overview

In-Line Installation

Panel Mount	Pipe, Tank, Wall Mount	4 to 20 mA Output*	Automation System	Field (Integral) Mount*
<p>Signet Instruments with 2850 Sensor Electronics</p> <ul style="list-style-type: none"> - 8900 - 9900 or with 3-9900.394 Direct Conductivity/Resistivity Module - 9950 with 9950.394 Direct Conductivity/Resistivity Module or with 3-9950.394-2 Dual Channel Conductivity Module 	<p>Signet Instruments with 2850 Sensor Electronics</p> <ul style="list-style-type: none"> - 9900 and Rear Enclosure or with 3-9900.394 Direct Conductivity/Resistivity Module and Rear Enclosure 	<p>Signet 2850 Sensor Electronics with</p> <ul style="list-style-type: none"> - Customer Supplied Programmable Logic Controller or - Programmable Automation Controller 	<p>Signet 2850 Sensor Electronics with</p> <ul style="list-style-type: none"> - 0486 Profibus Concentrator and - Customer Supplied Programmable Logic Controller or - Programmable Automation Controller 	<p>Signet Instrument</p> <ul style="list-style-type: none"> - 9900 with 3-9900.394 Direct Conductivity/Resistivity Module, 3-9900.396 angle adapter and 3-8052 Integral Mount Kit 






Signet 2839-2842 Conductivity Electrodes



Customer Supplied Fittings, 3/4 in. NPT or ISO threaded

All Sold Separately

Submersible Installation

Panel Mount	Pipe, Tank, Wall Mount	Field (Integral) Mount	4 to 20 mA Output*	Automation System
<p>Signet Instruments with 2850 Sensor Electronics</p> <ul style="list-style-type: none"> - 8900 - 9900 or with 3-9900.394 Direct Conductivity/Resistivity Module - 9950 with 9950.394 Direct Conductivity/Resistivity Module or with 3-9950.394-2 Dual Channel Conductivity Module 	<p>Signet Instruments with 2850 Sensor Electronics</p> <ul style="list-style-type: none"> - 9900 and Rear Enclosure or with 3-9900.394 Direct Conductivity/Resistivity Module, Rear Enclosure and customer supplied pipe extension or conduit with 3/4 in. FNPT threads* 	<p>Signet Instrument</p> <ul style="list-style-type: none"> - 9900 with 3-9900.394 Direct Conductivity/Resistivity Module, 3-9900.396 angle adapter and 3-8052 Integral Mount Kit 	<p>Signet 2850 Sensor Electronics with</p> <ul style="list-style-type: none"> - Customer Supplied Programmable Logic Controller or - Programmable Automation Controller 	<p>Signet 2850 Sensor Electronics with</p> <ul style="list-style-type: none"> - 0486 Profibus Concentrator and Customer Supplied Programmable Logic Controller or - Programmable Automation Controller 


Signet 2839-2842 Conductivity Electrodes



All Sold Separately

*Refer to the Signet Submersion Kit brochure (3-0000.707) located on our website for installation suggestions and options.


Operating Range Chart



Temperature/Pressure Graphs

Note:

The pressure/temperature graphs are specifically for the Signet sensor. During system design the specifications of all components must be considered. In the case of a metal piping system, the PVDF process connector provided with the sensor may reduce the overall system working pressure.



Application Tips

- Use 2839 series electrodes with the 3-2850-63 electronics and 8900 for applications requiring multiple measuring points.
- Liquid levels must be high enough to cover vent hole on sensor body.
- Install sensors in an area that will remain free of air bubbles and sediment build-up.
- Conductivity measurements are affected if electrodes are coated by process substances.

Ordering Notes

- 1) The Conductivity Certification tools are compatible with the following Signet Instruments: 8900, 9900, and 9950.
- 2) The sensor cable can be extended up to 30 m (100 ft). See restrictions under general specifications.

+GF+

Georg Fischer Signet LLC
Signet Conductivity/Resistivity Electrodes

Test Certificate

Part information

Code: 159 310 244
 Mfr. Part #: 3-2840.310-3
 Serial number: 61501061446
 Description: 0.1 cm², dual threaded, 1/4" NPT, PVDF
 Temperature Element: RTD PT1000
 Test date: 1/6/2015 2:36:23 PM

Measuring Standard(s)

ID#: RS-11
 Cal due date: 7/14/2015

Test Conditions

KCl solution concentration: 203.50 μS
 Solution temperature: 24.46°C


Test Data

Cell constant: 0.992
 Temperature: 1.92°C

Example of Test Certificate

Please refer to Wiring, Installation, and Accessories sections for more information.

Ordering Information



Sensors for use with 9900, 9950 and 2850 instruments

Mfr. Part No.	Code	Cell Constant	Connection	Thread Size(s)	Cable Length
3-2839-1V	159 001 810	0.01 cm-1	Dual Threaded	¾ inch NPT	4.6 m (15 ft)
3-2839-1VD	159 001 811	0.01 cm-1	Dual Threaded	ISO 7/1-R 3/4	4.6 m (15 ft)
3-2840-1V	159 001 812	0.1 cm-1	Dual Threaded	¾ inch NPT	4.6 m (15 ft)
3-2840-1VD	159 001 813	0.1 cm-1	Dual Threaded	ISO 7/1-R 3/4	4.6 m (15 ft)
3-2841-1V	159 001 814	1.0 cm-1	Dual Threaded	¾ inch NPT	4.6 m (15 ft)
3-2841-1VD	159 001 815	1.0 cm-1	Dual Threaded	ISO 7/1-R 3/4	4.6 m (15 ft)
3-2842-1V	159 001 816	10 cm-1	Dual Threaded	¾ inch NPT	4.6 m (15 ft)
3-2842-1VD	159 001 817	10 cm-1	Dual Threaded	ISO 7/1-R 3/4	4.6 m (15 ft)

Special Order Options - Please consult the factory

Cable length extensions of up to 30 m (100 ft) are available.

For any sensor being used with the 2850-6X, cable length should not exceed 4.6 m (15 ft).

Accessories and Replacement Parts

Mfr. Part No.	Code	Description
3-2850.101-1	159 001 392	Plug-in NIST Traceable Recertification Tool, 1.0 µS Simulated, for use with 8900, 9900, 9950, 2850 and the 2850 4-20 mA output
3-2850.101-2	159 001 393	Plug-in NIST Traceable Recertification Tool, 2.5 µS Simulated, for use with 8900, 9900, 9950, 2850 and the 2850 4-20 mA output
3-2850.101-3	159 001 394	Plug-in NIST Traceable Recertification Tool, 10.0 µS Simulated, for use with 8900, 9900, 9950, 2850 and the 2850 4-20 mA output
3-2850.101-4	159 001 395	Plug-in NIST Traceable Recertification Tool, 18.2 MΩ Simulated, for use with 8900, 9900, 9950, 2850 and the 2850 4-20 mA output
3-2850.101-5	159 001 396	Plug-in NIST Traceable Recertification Tool, 10.0 MΩ Simulated, for use with 8900, 9900, 9950, 2850 and the 2850 4-20 mA output
3-2850-61	159 001 400	Universal Junction Box, Conductivity Electronics, digital (S ³ L) output
3-2850-62	159 001 401	Universal Junction Box, Conductivity Electronics, 4 to 20 output
3-8052	159 000 188	¾ in. Integral Mounting Kit
5523-0322	159 000 761	Sensor cable (per ft), 3 cond. plus shield, 22 AWG, for cable extension through a junction box for the following sensors: 3-2840, 3-2841, 3-2842
3-8050-1	159 000 753	Universal Mount Junction Box