

# TCT 65 Centrifugal Pump



200 Newsome Drive  
Yorktown, VA 23693  
1-800-535-4243  
[www.Travaini.com](http://www.Travaini.com)



<b>Head Capacity</b>	28-184 Feet
<b>Capacity</b>	Up to 625 GPM
<b>Features</b>	Semi-open impeller design allows for the handling of viscous liquids
<b>Shaft Sealing</b>	Mechanical seal (std.) Double mechanical seal Packed stuffing box
<b>Options</b>	Bareshaft pump Coupled to electric motor Spacer coupling Monoblock
<b>Temperature</b>	GS & RA: -20°C-280°C A3, HC, & DU: -40°C-280°C

## Technical Data

PUMP TYPE		TCT65-160		TCT65-200		TCT65-250	TCT65-315
Head, max	Ft	43	155	63	260	115	180
Capacity, max	GPM	420	790	500	900	560	640
Speed	RPM	1750	3500	1750	3500	1750	1750

## Standard Materials of Construction\*\*

Part No.	Description	GS	RA	A3	HC	DU
102	Pump casing	Ductile iron			Hastealloy C	ASTM-CN7M
135	Wear plates	-	Cast iron			
161	Casing cover	Ductile iron				
210	Shaft	Stainless steel AISI 316			Incoloy 825	
230	Impeller				ASTM-CN7M	
330	Bearing housing	Cast iron				
524	Shaft sleeve	Stainless steel AISI 316		Hastealloy C	Incoloy 825	

## Model Designation

TCT65-200 A/1X-C/A3	
T	Travaini manufacturer
C	Monostage centrifugal pump
T	Open vortex impeller
65	Discharge flange size (mmm)
200	Nominal diameter of impeller (mm)
A	Modification of hydraulic design
1X	Constructive project number
C	Shaft sealing: C—Single mechanical seal 2C— Double mechanical seal
A3	Materials of construction

\*\*Special materials available upon request  
--For further information please consult Travaini Pumps USA.