



For pressure regulation

Alfa Laval SB Tank Pressure Regulator

Concept

The Tank Pressure Regulator is typically used on tanks within the brewing industry. The purpose of the regulator is to maintain and regulate top pressure on pressure tanks during filling, processing and emptying.

Working principle

The valve unit is supplied with variable setting, the relieving pressure is adjusted to the required working pressure in the tank. When tank top pressure exceeds preset pressure, gas leaves the regulator through the vent port either for atmospheric discharge or for collection. If the tank top pressure decreases, gas is supplied through the gas supply connection at the bottom.

Standard design

The pressure regulator comprises a single valve unit including pressure exhaust valve, pressure supply valve and connection for pressure gauge. On top is a vent port with outlet connection. Tank connection at side branch is normally connected to the pipe leading to the tank top. It is also possible to incorporate the Tank Pressure Regulator in a flow panel.



TECHNICAL DATA

Nominal size	Pressure range	Recommend filling/emptying speed	Working capacity of fermentation*
1"	0.2-4.0 bar	25 m³/h	100 m³
1½"	0.2-4.0 bar	50 m³/h	200 m³
2"	0.2-4.0 bar	100 m³/h	400 m³
3"	0.2-4.0 bar	200 m³/h	800 m³

* At max. fermentation rate 2.4 deg. Plato / 24 hrs.

PHYSICAL DATA

Materials
Product wetted steel parts: EN 1.4307 (AISI 304L)
Product wetted seals: EPDM

Connections
Union acc. DIN 11851
Union IDF acc. ISO 2853
Union SMS Swedish Standard Union
Clamp ferrule acc. ISO 2852

Cleaning in place (CIP)

Cleaning of the Tank Pressure Regulator is necessary before the next batch. The Tank Pressure Regulator is incorporated in the tank CIP procedure by means of the CIP adaptor. Before cleaning, the CIP adaptor is mounted on the pressure regulator whereby gas supply valve and pressure relief valve are forced open and fully cleaned in bypass. During the CIP procedure, all functions are blocked. See schematic drawing of the regulator.

Options


Pos. 1: CIP bend

Pos. 2: CIP T-piece

Pos. 3: Protection valve for pressure gauge

Pos. 4: Pressure gauge

Mounting bracket



Alfa Laval reserves the right to change specifications without prior notification. ALFA LAVAL is a trademark registered and owned by Alfa Laval Corporate AB.

ESE02919EN 1507

© Alfa Laval

How to contact Alfa Laval

Contact details for all countries are continually updated on our website. Please visit www.alfalaval.com to access the information direct.