

DATA SHEET







Please call:

BURT PROCESS EQUIPMENT 800-577-8111 for SALES and SUPPORT.

Click here to return to website





It's kind of a big deal

















- Programmable LED Colors with SunBright® Technology for Outdoor Applications
- ⊗ 8 Levels of Brightness | Extra Large LED Numbers
- **⊘** Signal Peak Value Detection | Dampens Noise
- **⊘** 6 SimplConnect® Cord Grips Included | No Add Ons
- **②** Relay Lights & Audible Alarm Function
- NEMA 4X Enclosure





The TVU Series Process Display isn't just rugged and reliable — it's a giant in the world of (multi)color displays.



TVU Series — Universal Process Display

The TVU Series Multi-Color LED Level Process Display and Controller is among the industry's most rugged and reliable wall-mount remote level displays.


LevelPro® TVU Series comes as a complete all-in-one unit that's ready to use right out of the box. Included is a vivid SunBright® LED Display with adjustable color and brightness, NEMA 4X enclosure, polycarbonate faceplate, a full set of SimplConnect® cord grips and corrosion-free plastic captive screws.

The industrial design of the TVU Series ensures that it will withstand the industry's most corrosive environments while remaining highly visible and easy to read.

Available with either 4 relay outputs or 2 relay + 4-20mA output, the TVU Series is great for automating your tank level processes.

Multi-color Display

- Acts as a Stack Light
- Colors Mimic ProcessConditions
- Industry's Largest Multi-Color LED Display



Specifications

General		
Display	LED 4 x 20mm High Red Adjustable Brightness	
Displayed Values	-999 ± 9999	
Transmission Parameters	1200115200 bit/s, 8N1 / 8N2	
Protection Class	NEMA 4X IP67	
Housing Material	Polycarbonate	
Input Signal Supply		
Standard	Universal Input: 0 4-20mA 0-10V 0-150mV RTD PH	
Voltage	85 - 260V AC/DC 16 - 35V AC, 19 - 50V DC*	
Output Signal Supply		
Standard	4 x Relays (5A) 2 x Relay (5A) + 4-20mA	
Voltage	24VDC	
Passive current output *	4-20mA (Operating Range Max. 2.8 - 24mA)	
Performance		
Accuracy	0.1% @ 25°C One Digit	
Temperatures		
Operating Temperatures	-40°F - 158°F -40°C - 70°C	


* optional

3




Wiring — Pin Assignment





Dimensions



Model Selection

TVU — Universal Multi-Color LED Display			
Part Number	Input	Output	
TVU-1421	4-20mA	4 Relay	
TVU-1429	4-20mA	4-20mA + 2 Relay	