

FICHA TÉCNICA CINTILLOS HONT

CINTILLOS COLOR NEGRO (Poliamida 6.6 UV Estabilizado)



CÓDIGO	PRESENTACIÓN	LARGO (mm)	ANCHO* (mm)	RESISTENCIA
H-HT-100x2.5-UV	Bls x 100 u	100 mm	2.5 mm	11kg
H-HT-150x3.6-UV	Bls x 100 u	100 mm	2.5 mm	24 kg
H-HT 200x3.6-UV	Bls x 100 u	200 mm	3.6 mm	24 kg
H-HT-200x4.8-UV	Bls x 100 u	200 mm	4.8 mm	34 kg
H-HT-250x4.8-UV	Bls x 100 u	250 mm	4.8 mm	34 kg
H-HT-300x4.8-UV	Bls x 100 u	300 mm	4.8 mm	24 kg
H-HT-300x7.6-UV	Bls x 100 u	300 mm	7.6 mm	34 kg
H-HT-370x7.6-UV	Bls x 100 u	370 mm	7.6 mm	72 kg
H-HT-380x4.8-UV	Bls x 100 u	380 mm	4.8 mm	72 kg
H-HT-380x7.6-UV	Bls x 100 u	380 mm	7.6 mm	34 kg
H-HT-400x7.6-UV	Bls x 100 u	430 mm	7.6 mm	72 kg
H-HT-430x4.8-UV	Bls x 100 u	430 mm	4.8 mm	55 kg
H-HT-500x4.8-UV	Bls x 100 u	500 mm	4.8 mm	34 kg
H-HT-500x7.6-UV	Bls x 100 u	500 mm	7.6 mm	34 kg
H-HT-550x9.0-UV	Bls x 100 u	550 mm	9.0 mm	72 kg
H-HT-610x4.8-UV	Bls x 100 u	610 mm	4.8 mm	104kg
H-HT-650x9.0-UV	Bls x 100 u	650 mm	9.0 mm	104 kg
H-HT-670x4.8-UV	Bls x 100 u	670 mm	4.8 mm	104 kg
H-HT-750x9.0-UV	Bls x 100 u	750 mm	9.0 mm	104 kg
H-HT-800x9.0-UV	Bls x 100 u	800 mm	9.0 mm	104kg
H-HT-900x9.0-UV	Bls x 100 u	900 mm	9.0 mm	104kg
H-HT-1000x4.8-UV	Bls x 100 u	1000 mm	9.0 mm	104 kg