

 weightechUSA

# WT-BT-BR complete

BLUETOOTH WEIGHING TRANSMITTER



WEIGHING DATA TRANSMITTER VIA BLUETOOTH  
**FAST, EFFICIENT AND EASY TO CALIBRATE**

wt-bt-br\_datasheet\_v01 - 04/24/25

Technical review: Loui Oriqui | Comercial review: Loui Oriqui

Edition: Stéphaney



# WT-BT-BR

## Bluetooth Weighing Transmitter

Easy to calibrate and configure using the free WT-BT-BR Cal and Android APPs



Polycarbonate housing

IP65 degree of protection

Connects up to 4 load cells

3 LED indicator lights for indicating low charge, Bluetooth connection and calibration

Auto-zero function


Adjustable digital filters available

Internal rechargeable battery


Provides 2 RS232 serial ports integrated into the equipment, for connection to ear tag readers and remote displays

Cattle weighing function



# CONNECTION



## APPLICATION EXAMPLE




## DIMENSIONS (in pol and mm)



# WTBT BR

## WEIGHING SYSTEM OVER BLUETOOTH TECHNOLOGY



## TECHNICAL DATA

A/D CONVERTER	
Application range	-0.1 ~ 4.0 mV/V
excitation voltage	5Vcc
Conversion rate (sampling speed)	30 a 480 samples per second
Internal resolution	1 / 1.000.000
POWER SUPPLY	
Charger	Entry: 100 — 240 VAC   Output: 12.6 VDC 1A
Internal battery	12 VDC 4400 mAh
Internal electronic supply voltage	8 — 13 VDC
OTHER SPECIFICATIONS	
Nominal temperature	-10 — +40°C
Degree of protection	IP65
Encapsulation material	Polycarbonate

## PART NUMBER

Products	Codes
WT-BT-BR Transmitter Complete	504335

### FIND US

10384 W State road 84 #6 - Davie, FL 33324

sales@weightechusa.com

weightechusa.com

**Technical Support:** +1 (954) 666-0877x302

**Sales:** +1 (954) 666-0877x305

### MORE INFO



[PRODUCT PAGE](#)