

**MODEL: 353101 - STAFF STATION**



353101

**FEATURES**

- Pushbutton for two-way intercom in audio-visual system with built-in Call-Assurance LED
- Speaker and microphone provide full-duplex audio to speak with the patient if desired
- Monitor LED
- Cancel button for localized call cancellation
- Interfaces with specialty beds via separate receptacle
- LED to indicate specialty bed is connected
- LED to indicate remote Pillow Speaker activity
- Output for lighting control options direct to low voltage lighting controller
- Continuous supervision of station for loss of data and/or power faults
- Plug-in connectors for easy service
- Bio-seal option to cover buttons and allow for easy disinfecting of the station

**SPECIFICATIONS**

**Power Required:** 75mA at 18v

**Weight:** 0.5 lb. (0.2 kg)

**Size: W:** 6.4" (16.2 cm)

**H:** 4.25" (10.8 cm)

**D:** 2.5" (6.4 cm), 0.5" (1.3 cm) off-wall

**Housing & Finish:** High-impact molded ABS 94-5VB; light gray faceplate

**Controls/Indicators:** One (1) Push button, One (1) Cancel button, One (1) Monitor LED, One (1) Call-assurance LED indicator, and One (1) Special Bed LED indicator, and One (1) Remote Pillow Speaker LED Indicator

**Terminations:** Plug-on connectors

**Backbox Options:** 3 gang (Non-gangable), 3-1/2" Deep

**DESCRIPTION**

The Staff Station typically located in a room or on a floor where staff members may be working. The station may also be used in patient areas such as day rooms or visitor's lounges or wherever call-in and two-way audio communication is desired. The station can also interface with a patient bed. The station provides a call-in pushbutton in the audio-visual system. The staff or patients communicate through the stations built-in speaker/microphone.

The Staff Station is connected to its associated corridor light or Domeless room controller and is continually supervised for both power and data. Through programming, a message can annunciate at the associated console(s) and / or the remote status application if a problem occurs.

*Architect and Engineer (A&E) Specifications available online at: [customerconnection.rauland.com](http://customerconnection.rauland.com)  
Specifications subject to change without notice*

©Copyright 2008 Rauland-Borg Corporation Printed in USA Rev 08/2008

USA-Mt.Prospect, IL  
Canada  
[www.rauland.com](http://www.rauland.com)

• 800-752-7725  
• 905-607-2335

• Fax 800-217-0977  
• Fax 905-607-3554



**Rauland-Borg Corporation**