

MODEL: 354001 - PULL CORD STATION



354001

FEATURES

- Plastic pull cord for easy activation
- Smooth, non-porous PVC coating on the cord provides an easily cleaned surface
- Call-Assurance LED
- Cancel button
- Water-resistant
- Large, easy to grab bell
- Continuous supervision of station
- Plug-in connectors for easy service

SPECIFICATIONS

Power Required: 4.8mA @ 18VDC

Weight: 0.2 lbs (0.10 kg)

Size: W: 3.1" (8.1 cm)

H: 4.25" (10.8 cm)

D: 0.6" (1.5 cm) in back box; 0.5" (1.3 cm) off-wall

Housing & Finish: High-impact molded Cycloloy 2950 UL 94-5VB; light grey faceplate

Controls/Indicators: One (1) pull cord for call actuation, One (1) Call-assurance LED, One (1) Cancel button

Terminations: Plug-on connector

Backbox Requirement: 1 gang (Non-gangable), 3 1/2" Deep

DESCRIPTION

The Pull Cord station is an emergency pull cord station that provides the ability to place a unique call-in priority from a single station by pulling on its plastic cord. The Pull-cord station is typically located in bathrooms near the toilet and in the shower. The membrane Cancel button allows for cancellation of the call at the station. Unit may utilize remote Cancel button(s) for ease of nurse call cancel when pull cord is mounted in an inaccessible location (e.g. ceiling). To make the station water-resistant, the station perimeter is caulked on three sides with sealant. It also has water diversion channels that open along the bottom of the station for drainage. The Pull-cord station is connected to its associated corridor light or Domeless room controller and is continually supervised.

*Architect and Engineer (A&E) Specifications available online at: customerconnection.rauland.com
Specifications subject to change without notice*

©Copyright 2008 Rauland-Borg Corporation Printed in USA Rev 08/2008