

MODEL: 354018 - 2 JACK STATION



354018

FEATURES

- Two (2) isolated inputs for auxiliary alarms with call-assurance LEDs
- Compatible with various 1/4" jack-compatible medical instruments
- Annunciate medical equipment alarms on pocket pagers, wireless phones, consoles, etc
- Each input can be configured as momentary or latched
- Programmable delay of call in
- Optional antimicrobial Bio-seal to cover cancel button and allow for easy disinfecting of the station
- Cancel button
- Annunciates cord-out

SPECIFICATIONS

Power Required: 11.5mA @18VDC

Weight: 0.25 lbs (0.1 kg)

Size: W: 3.2" (8.1" (8.0 cm)

H: 4.25" (10.8 cm)

D: 0.6" (1.5 cm in back box: 0.5" (1.3 cm) off-wall

Housing & Finish: High-impact molded Cycoloy 2950 UL 94-5VB; light grey faceplate

Controls/indicators: Two (2) 1/4" jacks, One (1) Cancel button, Two (2) call-placed LEDs

Terminations: Plug-on connector

Backbox Requirements: 1 gang (Non-gangable), 3 1/2" Deep

DESCRIPTION

The 2-Jack Station provides the ability to place two unique call priorities from a single station. The station is typically installed in patient rooms and monitors medical equipment that is routinely used. The 2-Jack Station allows an alarm from patient monitoring equipment to light corridor lights, tone and display at a console, as well as directly alert caregivers carrying wireless devices. Each 1/4" isolated jack is supervised, so if a piece of equipment is unplugged a call will be placed.

The 2-jack Station is also supervised for data and / or power faults and each jack is optically isolated from the alarming device and supports dry contact inputs.

*Architect and Engineer (A&E) Specifications available online at: customerconnection.rauland.com
Specifications subject to change without notice*

©Copyright 2008 Rauland-Borg Corporation Printed in USA Rev 08/2008

USA-Mt.Prospect, IL
Canada
www.rauland.com

• 800-752-7725
• 905-607-2335

• Fax 800-217-0977
• Fax 905-607-3554



Rauland-Borg Corporation