

SF301A, SF302 Call Cords

IL338 Specification Sheet

Tek-CARE® Nurse Call and Wireless Emergency Call Systems • Rev. 20 - 07/2016

Features

- UL® 1069 Listed; SF301A is also UL® 2560 Listed
- Oxygen safe
- Impact resistant and waterproof
- Small, lightweight pendant fits comfortably in hand
- Bed clips included



Description

The TekTone®SF301A (single) or SF302 (double) call cords are for use with the Tek-CARE® nurse call systems and wireless emergency call systems, where 1/4" phono jacks are used. Ten-foot cords are also available as SF301A/10 and SF302/10. The SF301A and SF302 are oxygen safe call cords certified safe for use by all patients receiving oxygen therapy. These waterproof and impact resistant call cords have completely sealed push buttons.



SF301A, SF302 Call Cords

Listings



SF301A is UL® 1069 and UL® 2560 Listed;
SF302 is UL® 1069 Listed;
UL® File Number E71599.

Specifications

Connection: 1/4(6.35 mm) plug-in phono jack
Construction: SPST-1A switch
Integral brass, fine silver contacts
1 AMP, 115 watt maximum, AC
Dimensions: 7' (2.13 m) long polyvinyl covered cord

Required Components

Tek-CARE®550 Wireless Nurse Call System
or
with SF561 or SF562 Room Stations
Tek-CARE®500 Wireless Emergency Call System
or
with SF530ES or SF530UL Room Stations
Tek-CARE® NC300™II Nurse Call System
or
with SF380A Patient Stations
Tek-CARE® NC200N or NC150N Nurse Call Systems
or
with IR151B or IR152B Patient Stations
Tek-CARE® NC110N Nurse Call System
with SF100C or SF102 Patient Stations