

SF301B Call Cord

IL1151 Specification Sheet

Tek-CARE Nurse Call and Wireless Nurse Call Systems • Rev. 3- 4/2025

Features

- | Tactile push-button call cord
 - Call button makes an audible and tactile click for assurance of activation
- | UL® 1069 Listed
- | Oxygen-safe
- | Impact-resistant and waterproof
- | Small, lightweight pendant fits comfortably in hand
- | Bed clips included
- | Call button makes an audible and tactile click for assurance of activation



SF301B Call Cord

Description

The TekTone SF301B Call Cord is for use with the Tek-CARE® nurse call systems and wireless emergency call systems where 1/4" phono jacks are used. The SF301B is an oxygen-safe call cord certified safe for use by all patients receiving oxygen therapy. These waterproof and impact-resistant call cords have completely sealed push buttons, and polyvinyl-covered cord.

Required Components

Tek-CARE® 3000 Nurse Call System with SF121 or SF122 Patient Stations
 Tek-CARE® 400 GEN3 Nurse Call System with SF121 or SF122 Patient Stations
 Tek-CARE® 500 Wireless Nurse Call System with SF521UL
 Tek-CARE® 120 Nurse Call System with SF121 or SF122 Patient Stations
 Tek-CARE® 300II Nurse Call System with SF380A Patient Stations
 Tek-CARE® NC200N or NC150N Nurse Call Systems with IR151B or IR152B
 Tek-CARE® NC110N Nurse Call System with SF100C or SF102 Patient Stations

Specifications

Dimensions:	SF301B:	8'long
	SF301B/10:	10'long
	SF301B/20:	20'long
Construction:	SPST-1A switch, Integral brass, fine silver contacts 1 AMP, 115 watt maximum	
Connections:	1/4" (6.35 mm) plug-in phono jack	

Listings



UL® 1069 Listed; UL® File Number E165723.