

SF401B Call Cord

IL1152 Specification Sheet

Tek-CARE Nurse Call and Wireless Nurse Call Systems • Rev. 0 - 4/2025

Features

- | Tactile push-button call cord
- Call button makes an audible and tactile click for assurance of activation
- | UL® 1069 Listed
- | Oxygen-safe
- | Impact-resistant and waterproof
- | Small, lightweight pendant fits comfortably in hand
- | Bed clip included
- | 8-pin DIN plug

Description

The TekTone SF401B call cord is for use with the Tek-CARE3000, Tek-CARE400 P5/P5+/GEN3, and Tek-CARE300III Nurse Call Systems, where 8-pin DIN jacks are used. The SF401B is an oxygen-safe call cord that is certified safe for use by all patients receiving oxygen therapy.

This waterproof and impact-resistant call cord has a completely sealed push button and a polyvinyl-covered cord.

Required Components

Tek-CARE®3000 Nurse Call System with IR331 or IR332 Patient Stations

Tek-CARE400® GEN3 Nurse Call System
IR430G3, IR431G3/IR432G3, IR434G3 patient stations

Tek-CARE400® Nurse Call System
IR411, IR412, IR412EPB patient stations

Tek-CARE400® P5/P5+ Nurse Call System
IR411P5/IR421P5, IR412P5/IR422P5 patient stations

Tek-CARE®300III Nurse Call System
IR319B, IR320B patient stations



SF401B Call Cord

Specifications

Dimensions:	SF401B:	8' long
	SF401B/10:	10' long
	SF401B/20:	20' long
Connection:	8-pin DIN plug SPST1-A switch	
Construction:	Integral brass, fine silver contacts 1 AMP, 15 watt maximum	

Listings



UL®1069 Listed and cUL® Listed to CSA
C22.2 No.205; UL® File Number E165723.