

TekTone SF573

Single Bed Multifunction Station

Description

The SF573 is a wireless, surface-mountable station that includes a Call button, a pull cord, an LED for call indication, and a Reset button. The SF573 also has three additional call buttons for Staff Emergency, Check-In, and Rounding.

When a call is placed, it annunciates on any master stations, duty stations, staff apps, and monitors installed on the Tek-CARE system zoned to display the call. The SF573 stations are configured using the LS450 Config Tool software. By default, the push button and handset place an "Emergency" call.

The SF573 may be directly surface-mounted to a non-metallic surface, or mounted using a non-metallic single-gang backbox or low voltage ring.

Features

- Call and Reset button
- IP65 water resistant
- In addition to the Call button, buttons are provided for Staff Emergency, Check-In, and Rounding
- Includes screws, anchors, and a wall-mount bracket
- Long-lasting and replaceable battery
- Low battery indication
- Optional pull cord (SF574) installed

Required Components

- NC570 Receiver
- NC571 Repeater

Optional Components

- SF574 Call Cord



SF573
Single Bed Multifunction Station

Technical Specifications

- **Dimensions:** 4.2"H × 3.4"W × 0.86"D (106 mm × 87 mm × 22 mm)
- **Connections:** RJ12 4P4C jack for SF574
- **Battery:** BA007 ×2 (CA2477)
- **Mounting:** Surface-mounted; attach back plate to a standard plastic single-gang ring or single-gang box. Do not use the metal rings or boxes as it interferes with the wireless signal.
- **Construction:** PC board with quality electronic components.