

MODEL: CLA214D — DUTY 4-BULB CORRIDOR LIGHT



CLA214D
(Patent # 6,693,514)



FEATURES

- Generates the necessary tones when used in conjunction with the R4KDY — Duty Station
- LED visual indication for high visibility, long life, low maintenance and low power consumption
- Programmable colors and flash rates to indicate pending calls, service requirements, and staff presence
- Supports up to six (6) call-in stations, one (1) of which can have audio capability
- Module status LED indicates when unit is not functioning properly
- Serves as hub for all room wiring

SPECIFICATIONS

Power Required: 15.5V @ 158 mA

Weight: 0.50 lbs. (0.23 kg)

Size: W: 5.48" (10.87 cm)

H: 4.28" (13.92 cm)

D: 3.80" (9.65 cm)

Housing and Finish: Lens – Xantar 18B Optical Clear
Face/Base – GE Cycology 2950 White

Controls: Module status LED
K-bus DIP switch address

Terminations: Modular plug-on connectors (power, data, audio)

Number of lamps: Four (4) (white, green, red, blue)

Backbox Requirements: Steel City 58371 3/4R, Raco 561, or any other single gang backbox. Mounting plate allows for North American, South American, and European style single and dual gang backboxes.

Certification: UL/C-UL 1069
FCC Part 15 Class A

DESCRIPTION

The CLA214D is typically located outside staff areas where a R4KDY provides visual indication of calls originating from bedside, bath/emergency, and code stations as well as service requirements and staff registrations. The R4KDY annunciates tones and reflects illuminated LEDs generated on the CLA214D. The CLA214D supports up to five (5) non-audio stations and one (1) R4KDY Duty Station.

The CLA214D provides a high-visibility annunciation of patient calls. The LEDs also provide long life, low maintenance, and low power consumption. This corridor light comes equipped with a module status LED, visible to service personnel, to indicate when the unit is not functioning properly. The mounting plate conveniently fits a variety of single and dual gang backboxes.

The corridor light is continuously supervised for both power and data signal.

ASSOCIATED EQUIPMENT

R4KDY — Duty Station

R4KTMB — K-bus Termination Board

R4KPR400 — Power Supply

Architects and Engineers Specifications available on disk. Specifications subject to change without notice.

Rauland-Borg Corporation

3450 West Oakton Street • Skokie, IL 60076-2958 • (847) 679-0900 • (847) 679-4106 Fax • www.rauland.com
In Canada: 4025 Sladeview Crescent, Units 4-6 • Mississauga, ON CANADA L5L 5Y1 • (905) 607-2335 • (905) 607-3554 Fax

