

MODEL: R4K12A — SINGLE BED STATION



R4K12A



FEATURES

- Over four (4) call-in priorities available
- DIN receptacle for patient nurse call and entertainment controls
- Monitor LED and Call-Assurance LED with Cancel button
- No dummy plugs required
- Continuous supervision for station presence
- Plug-in connectors for easy service
- Unique mounting plate design accommodates a variety of single and dual gang backboxes

SPECIFICATIONS

Power Required: 15.5V DC @ 5mA

Weight: 0.30 lb. (0.14 kg)

Size: W: 4.21" (10.69 cm)

H: 5.46" (13.87 cm)

D: 1.17" (2.97 cm)

Housing & Finish: High-impact molded ABS94VO; light gray faceplate

Controls: One (1) DIN receptacle
 One (1) Cancel button
 One (1) Monitor LED indicator
 One (1) Call-Assurance indicator

Terminations: Plug-on connectors

Backbox Options: Raco 561; Steel City 58371 3/4R or any other single gang backbox. Mounting plate allows for North American, South American, and European style single and dual gang backboxes

Certification: UL/C-UL 1069

DESCRIPTION

The R4K12A is a single bed station that allows both patients and staff to place different call-in priorities, depending on their requirements, to the assigned console(s). The bed stations can interface with call cords and entertainment speakers to initiate calls, provide entertainment control and allow intercom to the console over the station speaker. The bed stations can also allow intercom to the console over the bed rails or entertainment speaker with the addition of a R4KFB1 — Feature Bed Interface.

The bedside station is connected to its associated corridor light or domeless room controller and is continually supervised for station presence. Through programming, a "Trouble" message can annunciate at the associated console(s) when the station is removed from the system.

ASSOCIATED EQUIPMENT

- CLA222 / CLA244 — Audio Corridor Lights
- DCA200 / DCA216 — Audio Domeless Room Controllers
- NCESTV / NCDSTV — Pillow Speakers
- CCDIN — Call Cord
- R4KFB1 — Feature Bed Interface

Architects and Engineers Specifications available on disk. Specifications subject to change without notice.

Rauland-Borg Corporation

3450 West Oakton Street • Skokie, IL 60076-2958 • (847) 679-0900 • (847) 679-4106 Fax • www.rauland.com
 In Canada: 4025 Sladeview Crescent, Units 4-6 • Mississauga, ON CANADA L5L 5Y1 • (905) 607-2335 • (905) 607-3554 Fax

