

MODEL: R4K13VAHZ — HORIZONTAL SINGLE ENHANCED AUDIO BED STATION



R4K13VAHZ



FEATURES

- Over four (4) call-in priorities available
- DIN receptacle for patient entertainment controls and pillow speaker intercom with entertainment muting during nurse call
- Interfaces with specialty beds via separate receptacle
- Monitor LED and call-assurance LED with cancel button
- No dummy plugs required
- Continuous supervision for station presence
- Plug-in connectors for easy service
- Unique mounting plate design accommodates a variety of single and dual gang backboxes
- Single point output for lighting controller or radio stepper attachment
- Interface for full lighting control options with additional control module and pillow speakers

SPECIFICATIONS

Power Required: 15.5V DC @ 25mA

Weight: 0.30 lb. (0.14 kg)

Size: W: 5.46" (13.87 cm)

H: 4.21" (10.69 cm)

D: 1.17" (2.97 cm)

Housing and Finish: High-impact molded ABS94VO; light gray faceplate

Controls: One (1) DIN receptacle, One (1) Cancel button, One (1) Monitor LED indicator, and One (1) Call-assurance indicator

Terminations: Plug-on connectors

Backbox Options: Raco 561; Steel City 58371 3/4R or any other single gang backbox. Mounting plate allows for mounting to North American, South American, and European style single and dual gang backboxes

NOTE: If using lighting control, additional backbox space is required

Certification: UL/C-UL 1069

DESCRIPTION

The R4K13VA is a horizontal single bed station that allows patients to place call-ins to the assigned console(s). The bed stations can interface with call cords or entertainment speakers or specialty beds to initiate calls, control lighting, provide entertainment control and allow intercom to the console over the station speaker. When used with the NCES/NCDS Series Pillow Speakers, audio capabilities are transferred to the Pillow Speakers. When used with the R4KFB1 – Feature Bed Interface, the audio capabilities are transferred to the bed rail with entertainment muting in the pillow speakers if used. The addition of the R4KSLC1 allows for full lighting control options through buttons on a pillow speaker.

The bedside station is connected to its associated corridor light or domeless room controller and is continually supervised for station presence. Through programming, a "Trouble" message can annunciate at the associated console(s) when the station is removed from the system.

Architects and Engineers Specifications available on disk. Specifications subject to change without notice.

ASSOCIATED EQUIPMENT

CLA222, CLA244 – Audio Corridor Lights

DCA200, DCA216 – Audio Domeless Room Controllers

NCES/NCDS – Pillow Speakers Series

R4KSLC1 – Single Lighting Control Module

CCDIN – Call Cord

R4KFB1 – Feature Bed Interface

NCLV120/NCLV240 – High Voltage Light Switch Controller

Rauland-Borg Corporation

3450 West Oakton Street • Skokie, IL 60076-2958 • (847) 679-0900 • (847) 679-4106 Fax • www.rauland.com
 In Canada: 4025 Sladeview Crescent, Units 4-6 • Mississauga, ON CANADA L5L 5Y1 • (905) 607-2335 • (905) 607-3554 Fax

