

**MODEL: R4K14SA — SINGLE BED STATION
W/STAFF EMERGENCY - AUDIO**



R4K14SA



FEATURES

- Functions as single bed station with staff emergency pushbutton
- Over 4 call-in priorities available
- DIN receptacle for patient nurse call and entertainment controls
- Monitor LED and two call-assurance LED's with cancel button
- No dummy plugs required
- Continuous supervision for station presence
- Plug-in connectors for easy service
- Unique mounting plate design accommodates for a variety of single and dual gang backboxes

SPECIFICATIONS

Power Required: 15.5V DC @ 7mA

Weight: 0.25 lb. (0.11 kg)

Size: W: 4.21" (10.69 cm)
H: 5.46" (13.87 cm)
D: 1.17" (2.97 cm)

Housing and Finish: High-impact molded ASBS94VO; light gray faceplate

Controls: One (1) DIN receptacle, One (1) Emergency pushbutton, One (1) Cancel button, One (1) Monitor LED indicator, and Two (2) Call-assurance indicators

Terminations: Plug-on connectors

Backbox Options: Raco 561, Steel City 58371 3/4R or any other single gang backbox. Mounting plate allows for mounting to North American, South American, and European style single and dual gang backboxes

Certification: UL/C-UL 1069

DESCRIPTION

The R4K14SA is a single bed station with the added capability of placing an emergency call. The station also allows patients and staff to place different call-in priorities, depending on their requirements, to the assigned console(s). The bed stations can interface with call cords and entertainment speakers to initiate calls, provide entertainment control and allow intercom to the console over the station speaker.

The bedside station is connected to its associated corridor light or domeless room controller and is continually supervised for station presence. Through programming, a "Trouble" message call can annunciate at the associated console(s) when the station is removed from the system.

ASSOCIATED EQUIPMENT

- CLA222, CLA244 – Audio Corridor Lights
- DCA200, DCA216 – Audio Domeless Room Controllers
- NCESTV/NCDSTV – Pillow Speakers
- CCDIN – Call Cord

Architects and Engineers Specifications available on disk. Specifications subject to change without notice.

Rauland-Borg Corporation

3450 West Oakton Street • Skokie, IL 60076-2958 • (847) 679-0900 • (847) 679-4106 Fax • www.rauland.com
In Canada: 4025 Sladeview Crescent, Units 4-6 • Mississauga, ON CANADA L5L 5Y1 • (905) 607-2335 • (905) 607-3554 Fax



MODEL: CCDIN — CALL CORD — DIN



CCDIN



FEATURES

- One (1) monetary push button switch in a light grey, high impact molded plastic housing with a red switch cap
- 8-pin DIN connector and strain relief cable
- Shockproof and may be safely washed or sterilized
- Approved for use in oxygen rich environments

SPECIFICATIONS

Weight: 0.40 lbs. (0.18 kg)

Size: Length: 10 ft (3.05 m)

Housing: High-impact molded plastic in light grey with red switch cap

Terminations: 8-pin DIN connector

Certification: UL/C-UL 1069

DESCRIPTION

The CCDIN — Call Cord is used in conjunction with Responder patient stations. With an 8-pin DIN connector, the CCDIN plugs securely into the patient stations to provide a unique call-in priority that can be customized based on a facility's needs. The call cord is shockproof and made of high impact molded plastic which makes the cord readily cleaned and sterilized.

Engineering Specifications available on disk. Specifications subject to change without notice.

Rauland-Borg Corporation

3450 West Oakton Street • Skokie, IL 60076-2958 • (847) 679-0900 • (847) 679-4106 Fax • www.rauland.com
In Canada: 4025 Sladeview Crescent, Units 4-6 • Mississauga, ON CANADA L5L 5Y1 • (905) 607-2335 • (905) 607-3554 Fax

