

MODEL: R4KCNCL — CANCEL STATION



R4KCNCL



FEATURES

- One (1) Cancel touchpoint
- Flexible programming for cancellation of calls
- Continuous supervision for station presence
- Unique mounting plate design accommodates a variety of single and dual gang backboxes
- Plug-in connectors for easy service

SPECIFICATIONS

Power Required: 15.5V DC @ 0mA

Weight: 0.20 lb. (0.09 kg)

Size: W: 4.21" (10.69 cm)

H: 5.46" (13.87 cm)

D: 1.17" (2.97 cm)

Housing & Finish: High-impact molded ABS94VO;
light gray faceplate

Controls: One (1) Cancel touchpoint

Terminations: Plug-on connectors

Backbox Options: Raco 561, Steel City 58371 3/4R or any other single gang backbox. Mounting plate allows for North American, South American, and European style single and dual gang backboxes

Certification: UL/C-UL 1069

DESCRIPTION

The R4KCNCL is a cancel station that can be programmed to cancel some or all call priorities placed from a room. The Cancel touchpoint cancels the call at the room and at the console.

The R4KCNCL is connected to its associated corridor light or domeless room controller and is continually supervised for station presence. Through programming, a "Trouble" message can annunciate at the associated console(s) when the station is removed from the system.

ASSOCIATED EQUIPMENT

CLA222 / CLA244 — Audio Corridor Lights

CLV122 / CLV144 — Visual Corridor Lights

DCV100 / DCV116 — Visual Domeless Room Controllers

DCA200 / DCA216 — Audio Domeless Room Controllers

Architects and Engineers Specifications available on disk. Specifications subject to change without notice.

Rauland-Borg Corporation

3450 West Oakton Street • Skokie, IL 60076-2958 • (847) 679-0900 • (847) 679-4106 Fax • www.rauland.com
In Canada: 4025 Sladeview Crescent, Units 4-6 • Mississauga, ON CANADA L5L 5Y1 • (905) 607-2335 • (905) 607-3554 Fax

