



R4KOUT4R



MODEL: R4KOUT4R — VISUAL OUTPUT CONTROLLER

FEATURES

- Contains 4 relay outputs for dry contact circuit connections
- Used in conjunction with the DCV100 6-point Visual Domeless Room Controller
- (4) 6-pin SL headers for output connection with wiring pig-tails for installation
- Contact points rated for 30 V DC/ 62.5 V AC @ 1A max.

SPECIFICATIONS

Power Required: 15.5V @ 32 mA

Weight: .11 lbs. (.051 kg)

Size: W: 3.36" (8.53 cm)
H: 3.91" (9.93 cm)
D: .57" (1.46 cm) for components – 1.00" (2.54 cm) at connector

Housing and Finish: PCB – no shrink-wrap cover

Terminations: SL 6 pin headers for each control output – 4 total - each contact: 30V DC/62.5 V AC @ 1A max.

Backbox Requirements: Mounts in DCV100 box on DCV100

Certification: UL/C-UL 1069

DESCRIPTION

The R4KOUT4R – Visual Output Controller provides 4 isolated, latched, normally open or normally closed relay contact outputs for dry contact circuit connections. It can be used to drive additional relays for high voltage control and general contact closure applications not appropriate for solid state relays. The output controller is used in conjunction with the DCV100 6-point Visual Domeless Room Controller.

ASSOCIATED EQUIPMENT

DCV100 – 6 point Audio Domeless Room Controller

Architects and Engineers Specifications available on disk. Specifications subject to change without notice.

Rauland-Borg Corporation

3450 West Oakton Street • Skokie, IL 60076-2958 • (847) 679-0900 • (847) 679-4106 Fax • www.rauland.com
In Canada: 4025 Sladeview Crescent, Units 4-6 • Mississauga, ON CANADA L5L 5Y1 • (905) 607-2335 • (905) 607-3554 Fax

