

MODEL: R4KSS — STAFF STATION



R4KSS



FEATURES

- Pushbutton for two-way intercom in audio-visual system
- Monitor LED and Call-Assurance LED with Cancel touchpoint
- Continuous supervision for station presence
- Plug-in connectors for easy service
- Unique mounting plate design accommodates a variety of single and dual gang backboxes

SPECIFICATIONS

Power Required: 15.5V DC @ 5mA

Weight: 0.35 lb. (0.16 kg)

Size: W: 4.21" (10.69 cm)

H: 5.46" (13.87 cm)

D: 1.17" (2.97 cm)

Housing & Finish: High-impact molded ABS94VO;
light gray faceplate

Controls: One (1) Cancel button
One (1) Monitor LED indicator
One (1) Call-Assurance indicator

Terminations: Plug-on connectors

Backbox Requirements: Raco 561, Steel City 58371 3/4R or any other single gang backbox. Mounting plate allows for North American, South American, and European style single and dual gang backboxes

Certification: UL/C-UL 1069

DESCRIPTION

The R4KSS is a staff station typically located in a room or on a floor where staff members may be working. The station may also be used in patient areas such as day rooms or visitor's lounges. Wherever call-in and two-way audio communication is desired, the station provides a call-in pushbutton in the audio-visual system. The staff or patients communicate through the stations built-in speaker/microphone.

The staff station is connected to its associated corridor light or domeless room controller and is continually supervised for station presence. Through programming, a "Trouble" message can annunciate at the associated console(s) when the station is removed from the system.

ASSOCIATED EQUIPMENT

CLA222 / CLA244 — Audio Corridor Lights

DCA200 / DCA216 — Audio Domeless Room Controllers

nder[®]

Architects and Engineers Specifications available on disk. Specifications subject to change without notice.

Rauland-Borg Corporation

3450 West Oakton Street • Skokie, IL 60076-2958 • (847) 679-0900 • (847) 679-4106 Fax • www.rauland.com
In Canada: 4025 Sladeview Crescent, Units 4-6 • Mississauga, ON CANADA L5L 5Y1 • (905) 607-2335 • (905) 607-3554 Fax

