

MODEL: CLV122 — VISUAL 2-BULB CORRIDOR LIGHT



CLV122
(Patent # 6,693,514)



FEATURES

- LED visual indication for high visibility, long life, low maintenance, and low power consumption
- Programmable colors and flash rates to indicate pending calls, service requirements and staff presence
- Supports six (6) non-audio call-in stations
- Module status LED indicates when unit is not functioning properly
- Serves as hub for all room wiring

SPECIFICATIONS

Power Required: 15.5V @ 62mA

Weight: 0.40 lbs. (0.18 kg)

Size: W: 5.48" (10.87 cm)
H: 4.28" (13.92cm)
D: 3.80" (9.65 cm)

Housing and Finish: Lens – Xantar 18B optical clear
Face/Base – GE Cycology[®] 2950 white

Controls: Module status LED
K-bus DIP switch address

Terminations: Modular plug-on connectors (power, data, audio)

Number of lamps: Two (2) (white, red)

Backbox Requirements: Steel City 58371 3/4R, Raco 561, or any other single gang backbox. Mounting plate allows for North American, South American, and European style single and dual gang backboxes.

Certification: UL/C-UL 1069;
FCC Part 15 Class A

DESCRIPTION

The CLV122 is typically located outside of patient and staff areas to provide visual indication of calls originating from bedside, bath/emergency, and code stations as well as service requirements and staff registrations. The colors and flash rates of the LEDs are fully programmable according to a facility's needs. The CLV122 provides support for six (6) non-audio call-in stations.

The CLV122 has unique LEDs to provide a high-visibility annunciation of patient calls. The LEDs provide a long life, low maintenance and low power consumption. The corridor light comes equipped with a module status LED, visible to service personnel, to indicate when the unit is not functioning properly. The mounting plate conveniently fits a variety of single and dual gang backboxes. The corridor light is continuously supervised for both power and data signal.

ASSOCIATED EQUIPMENT

R4KTMB — K-bus Termination Board

R4KPR400 — Power Supply

Architects and Engineers Specifications available on disk. Specifications subject to change without notice.

Rauland-Borg Corporation

3450 West Oakton Street • Skokie, IL 60076-2958 • (847) 679-0900 • (847) 679-0625 Fax • www.rauland.com
In Canada: 4025 Sladeview Crescent, Units 4-6 • Mississauga, ON CANADA L5L 5Y1 • (905) 607-2335 • (905) 607-3554 Fax

