

MODEL: R4KPB12 - SLIM PUSH FOR HELP STATION



R4KPB12

FEATURES

- Extra large back-lit button for easy activation
- Call-Assurance/Monitor LED
- Cancel button
- Plug-in connectors for easy service
- Continuous supervision of station
- Optional antimicrobial Bio-seal to cover buttons and allow for easy disinfecting of the station

SPECIFICATIONS

Power Required: 4mA @ 15VDC

Power Required when used with SLIM Speaker Module: 7mA @ 15VDC

Weight: 0.20 lbs. (0.09 kg)

Size: **W:** 3.2" (8.1 cm)

H: 4.25" (10.8 cm)

D: 0.6" (1.5 cm) in back box: 0.5" (1.3 cm) off-wall

Housing and Finish: High-impact molded Cyclooy 2950 UL 94-5VB; light grey faceplate

Controls/Indicators: One (1) Push button for call actuation, One (1) Call-assurance/Monitor LED, and One

(1) Cancel button

Terminations: Plug-on connectors

Backbox Requirement: : 1-gang, Non-gangable W: 2.25" (5.7 cm) H: 4" (10.2 cm) D: 3.5" (8.9 cm)

Backbox Requirement when used with SLIM Speaker Module: 3-gang, Non-gangable W: 5.5" (14 cm) H: 3.75" (9.5 cm) D: 3.5" (8.9 cm)

Certification: UL/C-UL 1069, FCC Part 15 Class B, IEC60601-1-2, Designed for compliance to IEC60601-1 and CE Marking (MDD), FDA Registered, and RoHS Compliant

DESCRIPTION

The Responder® 4000 SLIM Push for Help Station is a call pushbutton station providing the ability to place a call for help. Pressing the cancel button cancels the call. Using custom buttons, the station can be customized for unique call priorities such as: "Staff Assist," "Bath," "Help," etc.

The Push for Help station is connected to its associated corridor light and is continually supervised for station presence. Through programming, a "Trouble" message can annunciate at the associated console(s) when the station is removed from the system.

*Architect and Engineer (A&E) Specifications available online at: customerconnection.rauland.com
Specifications subject to change without notice*

©Copyright 2009 Rauland-Borg Corporation Printed in USA Rev 03/2009

USA-Mt.Prospect, IL
Canada
www.rauland.com

• 800-752-7725
• 905-607-2335

• Fax 800-217-0977
• Fax 905-607-3554



Rauland-Borg Corporation