Product Specification Sheet

JK300A, JK300/2 Monitor Call Interface

JK300A, JK300/2 Monitor Call Interface

DESCRIPTION

The JK300A Monitor Call Interface is for use in applications where a simple interface is needed to connect the monitor input of an IR300-series or IR400P5-series station to an external contact closure. The JK300A accepts a standard ¼" phono-type jacks and places a call if a plug is removed. A ¼" dummy plug is included for use when the monitor point is not connected to an external device. The JK300/2 Monitor Call Interface provides two ¼" jacks and two dummy plugs.

JK300A, JK300/2 Monitor Call Interface

SPECIFICATIONS

- Dimensions: Height: 4.5" (114 mm)
  Width: 2.75" (70 mm)
  Depth: 1.5" (38 mm)
  Projects: 0.25" (6.5 mm)
- Construction: Reliable components mounted on a flame-retardant (UL® 94V-0) plastic panel
- Connections: Wire lead pigtails
- Housing: Single-gang electrical box or ring

FEATURES

- Easy Installation
- Mounted on a flame-retardant (UL® 94V-0) plastic panel
- Simple, reliable operation

APPLICABLE COMPONENTS

- Tek-CARE®400 P5/P5+ Nurse Call System
  IR400P5/P5+-series Multipurpose, Patient, Resident,
  Check-In, Staff or Duty Stations
- Tek-CARE®400 Nurse Call System
  PM423 Auxiliary Input Module
  IR400-series Multipurpose, Patient, Resident,
  Check-In, Staff or Duty Stations
  Tek-CARE®NC300III Nurse Call System
  IR300-series Multipurpose, Patient, Staff or Duty Stations
- Tek-CARE®120 or 160 Nurse Call Systems
  PM123 Auxiliary Input Module

Toll-Free: 888.556.3998
Phone: 716.689.0871

Address: 5225 Sheridan Drive, Georgetown Square
Williamsville, New York 14221
E-mail: support@becsolutionsllc.com