NC554/15 PoE Network Switch

IL1137 Specification Sheet

Tek-CARE400 GEN3, Tek-CARE3000 Nurse Call Systems • Rev. 2 - 2/2025

Features

- 15 PoE+ ports provide a total of 231W of power for NC435G3 and NC331 Hubs
- Uninterrupted PoE keeps PoE power on even when the switch is updating firmware or performing software reboot
- Fanless and versatile mounting option (desktop and wall-mountable)
- Troubleshoot connection issues via cable test

Description

The NC554/15 PoE Network Switch provides communication and power to NC435G3 Hubs in the field while interfacing with the NC475 Tek-CARE® Appliance Server at the system head-end.

The NC554/15 is a managed switch supporting uninterruptable Power-Over-Ethernet (PoE) to help optimize the performance and troubleshooting of the network. The power supply for the device and PoE demands is included as shipped.

The new and improved business-friendly GUI allows easy management and simple configuration of the network interfacing field and head-end devices.

Required Components

NC475 Tek-CARE Appliance Server
NC435G3 Tek-CARE Hub, or NC331 Tek-CARE Hub

NC554/15 PoE Network Switch

Specifications

Dimensions:	11.26"H × 4.02"W × 1.06"D (286 mm × 102 mm × 27 mm)
Weight:	1.95 lb (0.883 kg)
Operating temperture:	32° to 104°F (0° to 40°C)
Humidity (relative):	90% maximum relative humidity (RH), non-condensing
Storage temperature:	-4° to 158°F (-20° to 70°C)
Housing:	Metal

Listings

UL® 1069 Listed; UL® File Number E71599.

FCC Part 15 class B.

CE/EN55032/24.

www.tektone.com
324 Industrial Park Road • Franklin, NC 28734 • tektone@tektone.com
Phone: 828.524.9967 • Fax: 828.524.9968 • Sales: Choose option 2 • Tech Support: Choose option 3
TekTone's quality system is registered to the ISO 9001:2015 standard.