



PK250B Power/Standby UPS

PK250B Power/Standby UPS

DESCRIPTION

The PK250B Uninterruptible Power Supply provides uninterrupted power in the event of utility power failures, brownouts and blackouts. It is for use with various nurse call systems, the NC450MICRO and NC455CE Central Equipment (CE) Modules, and the NC475 Tek-CARE Appliance Server. Its economical cost and compact size will enhance the operation of your system. When power is interrupted, the PK250B immediately cuts in to provide square wave power for any connected hardware until an emergency generator is activated or power is restored. In the event of a prolonged power outage, the PK250B will provide power to the limit of its battery. Battery backup for the NC475 Tek-CARE Appliance Server is rated for 10 minutes. The unit has distinctive alarms for on battery and battery low. Other features include output receptacles for connection of equipment, and power cord for a standard 120 volt, 15 AMP power circuit.

SPECIFICATIONS

- **Battery Output:**
 - Capacity: 600VA / 330 W
 - Voltage: 115 VAC +/-8%
 - Frequency: 50 or 60 Hz +/-0.1% (auto-sensing)
 - Connections: 5x 115 VAC battery backup + surge
 - 2x 115 VAC surge protection only
 - 1x USB battery backup + surge
- **Input:**
 - Voltage: 120 VAC
 - Frequency: 50 or 60 Hz
 - Connection: 5' cord with right angle plug
- **Battery:**
 - Type: Sealed, maintenance-free lead-acid
- **Size:**
 - Overall: 5.5" x 10.8" x 4.1"
 - Weight: 7.5 lbs.

APPLICABLE COMPONENTS

- NC356CE Central Equipment (Tek-CARE®NC300III Nurse Call System)
- NC450MICRO Central Equipment (Tek-CARE®400 Nurse Call System)
- NC455CE Central Equipment (Tek-CARE®400 P5+ Nurse Call System)
- NC475 Tek-CARE® Appliance Server

LISTINGS

- FCC Part 15 Class B, FCC Part 68, TUV, UL® 1778, UL® 2560