

## MODEL: R5K DOMELESS 16pt VISUAL



R5KDC016

### FEATURES

- Accommodates sixteen (16) station connection points for non-audio stations
- Designed for use where a corridor light is not needed
- Adds additional room stations in a ward environment
- Other corridor lights can be programmed to reflect calls placed on patient stations connected to a domeless controller
- Serves as control module for room stations
- Status LED indicates domeless controller operational status
- Fail-safe operation in event of loss of data communications
- Mounting plate design accommodates a variety of single and dual gang backboxes

### SPECIFICATIONS

**Power Requirements:** 15.5V DC @ 578 mA (max)

**Weight:** 1484 g (3.27 lbs)

**Size: W:** 15.87 cm (6.25")

**H:** 24.13 cm (9.5")

**D:** 9.52 cm (3.75")

**Housing and Finish:** 20 gauge steel, painted gray

**Controls/Indicators:** One (1) status LED

**Backbox Requirement:** The mounting hole pattern on the housing allows for North American, South American, and

European style single and dual gang backboxes. The metal housing also permits the R5KDC016 to be located above ceiling tiles or to be placed into a wall.

**Terminations:** Plug on connectors, CAT 5 and CAT 6 compatible

**Certifications:** Designed for compliance to ANSI/UL 1069, IEC 60950, CE, RoHS / WEEE Compliant. Assembled in a U.S. FDA Registered facility.

### DESCRIPTION

The R5KDC016 provides the connection points for up to sixteen (16) non-audio room stations and is typically located where a corridor light is not needed or desired. The domeless controller can be mounted in a wall cavity or ceiling outside of the patient room. Other corridor lights can be programmed to reflect calls placed on patient stations connected to the domeless controller.

The domeless controller will operate in a default fail-safe mode if communication with the Main System Controller is interrupted. It also contains a status LED visible to service personnel to indicate the device status. The mounting plate

accommodates a variety of backboxes. The domeless controller is continuously supervised for both power and data. A "Trouble" message will annunciate at the covering console(s) if the controller is removed from the system or becomes non-functional.



**Rauland**  
A Division of AMETEK, Inc.  
[www.Rauland.com](http://www.Rauland.com)

Toll Free +1 800 752 7725  
From Outside the U.S. +1 847 590 7100

*Architect and Engineer (A&E) Specifications available online at [customerconnection.rauland.com](http://customerconnection.rauland.com)  
Specifications subject to change without notice.*