

MODEL: PULLCORD ANTI-LIGATURE KIT



350033



FEATURES

- Anti-ligature cord breaks at 13 lbf +/- 3 lbf (57.8 N +/- 13.4 N)
- Pull ring designed to accommodate various disabilities
- Pullcord and pull rings contain anti-microbial additive
- Up to three pull rings allow placement on cord at multiple intervals
- Compatible with all Responder pullcord stations
- Quick and easy field replacement for existing pullcords

SPECIFICATIONS

Cord Material: TPU Thermoplastic Polyurethane Elastomer Polyether Base with nylon core and anti-microbial additive

Cord Length: 10 ft (3.04 m)

Cord Breakage: 13 lbf +/- 3 lbf (57.8 N +/- 13.4 N)

Pull ring Material: PC/ABS with anti-microbial additive

Pull ring Dimensions:

W: 3.43" (87.12 mm)

H: 3.13" (79.48 mm)

D: 0.40" (10.20 mm)

Pull ring Quantity: 3

Certification: CE, RoHS/WEEE.

The 350033 design satisfies the applicable advice and guidance of the *Health Technical Memorandum HTM 08-03: Bedhead Services*. In addition, the cord is designed to break at lower force than the requirement specified in *AS 3811 Hard-Wired Patient Alarm Systems*.

DESCRIPTION

The Pullcord Anti-Ligature Kit is ideal for applications where extra safety precautions are needed to minimize the risk of resident self-harm. The pullcord is designed to break with a low breaking force without elongation yet provides a secure connection point to the pullcord station. Three ergonomically designed pull rings accommodate placement of the resident's hand or other assistive devices at multiple intervals on the pullcord. The pullcord and pull rings contain an anti-microbial additive for infection control.

The Pullcord Anti-Ligature Kit is compatible with all Responder pullcord stations. The Pullcord Anti-Ligature Kit can be installed on existing pullcord stations without remov-

ing the station from the wall allowing easy conversion with minimal disruption in the patient room. The word "Rauland" is indelibly printed along the pullcord to distinguish it from standard Rauland pullcords.



Rauland
A Division of AMETEK, Inc.
www.Rauland.com

Toll Free +1 800 752 7725
From Outside the U.S. +1 847 590 7100

*Architect and Engineer (A&E) Specifications available online at customerconnection.rauland.com
Specifications subject to change without notice.*