

MODEL: R5K DUTY STATION



R5KSDTY



FEATURES

- One (1) Call button with Call Assurance LED
- Five (5) colored LEDs mimic the highest priority call on corridor lights within its coverage area
- Call tone indication of active calls are the same as nurse console
- Adjustable tone levels with mute control
- Optional antimicrobial Bio-seal to cover pushbuttons
- Continuous supervision for station presence
- Surface mount for easy installation
- Mounting design accommodates a variety of single and dual gang backboxes

SPECIFICATIONS

Power Requirements: 15.5V DC @ 40 mA

Weight: 141 g (4.9 oz)

Size: W: 11.97 cm (4.71")

H: 10.96 cm (4.31")

D: 2.38 cm (0.94")

Housing and Finish: Polycarbonate ABS, UL 94-5VA; light gray faceplate.

Controls/Indicators: One (1) Call button, One (1) Call Assurance LED, Five (5) colored LEDs, One (1) Monitor LED, and One (1) Cancel button.

DESCRIPTION

The R5KSDTY is usually mounted in a staff room or lounge where staff members require notification of active calls within the area. The station provides five colored LEDs to mimic the call priority and flash rate of corridor lights within its coverage area. Annunciation tones are provided along with a mute control. The tone is associated with the highest priority active call. A pushbutton allows for audio communication with the covering console. The Duty Station requires connection to a Duty Domeless Controller. The station may also be used for audio monitoring of a designated area.

The station is continuously supervised for station presence.

Backbox Requirement: Surface mountable; compatible with European, North American, South American single and dual gang boxes.

Terminations: Plug on connector, CAT 5 and CAT 6 compatible

Certifications: Designed for compliance to ANSI/UL 1069, IEC 60950, CE, RoHS / WEEE Compliant. Assembled in a U.S. FDA Registered facility.

A "Trouble" message will also annunciate at the covering console(s) if the station is removed from the system or becomes non-functional.