



WNC-SB Transmitter with Call Button

The WNC-SB transmitter with call button is a fully supervised 900 MHz spread spectrum transmitter equipped with a momentary alarm button. A call from a WNC-SB station activates a pre-programmed call information and an audible tone at the master station. Depending on console and output hardware selected the alarm information may be additionally sent to corridor/ zone lights, pocket pagers, cellular phones, two way radios, telephones, central monitoring station or via email. A mounting kit is provided for quick and easy installation.

Architects' and Engineers' Specifications

Transmitter shall be BEC Server WNC-SB with 900 MHz spread spectrum technology with proven frequency hopping transmissions for greater reliability. It shall be equipped with a momentary push button to transmit an alarm for panic button installation under counter or desk. Transmitter shall be fully supervised for battery voltage as well as operation.

Specification

- Housing: Height: 0.9"
Width: 1.7"
Depth: 3.5"
- Projects 15/32" (12mm) from mounting
- Weight: 1.7 oz. without battery
- Power: 3.0V lithium battery CR123A

Features

- Reliable 900 MHz spread frequency transmission
- Momentary push button
- For panic button installation under counter or desk.
- Typical battery life is 48 months
- Mounting kit for easy installation
- Fully supervised for battery voltage and operation

System Components

<u>Model No.</u>	<u>Description</u>
CR123A	Replacement 3V lithium battery
Server	Video Display Console
MV400	400Z Console Master
MV200	200Z Console Master
WNC-RP	Repeater/Locator