

ACCUTECH 950004-ID

BR Startup Kit | Centralized Wander Management Infrastructure Hub

PRODUCT OVERVIEW

The Accutech 950004-ID BR Startup Kit serves as a core hardware intelligence component within advanced wandering management and resident safety infrastructures. It is engineered to bridge the gap between physical perimeter sensors deployed at facility exits and localized control monitoring stations. By aggregating and processing automated security credentials and high-speed data telemetry from protected boundaries, it eliminates the operational complexity of managing individual entry points. This centralized topology ensures that large-scale senior care, nursing home, memory care, and hospital facilities maintain instantaneous, real-time situational awareness.

Deployed directly between peripheral zone controllers, transmitter wands, door controllers, and central administration frameworks, the 950004-ID module channels complex serial data traffic. This proactive routing method eliminates communication bottlenecks and guarantees that complex localized actions—such as authorized staff bypass, secure visitor access, and localized security overrides—are instantly synchronized with perimeter sensors. This active tracking processing ensures absolute protection across expansive hospital wings, long care facility corridors, and high-risk resident zones by establishing an uncompressed, bidirectional data pipeline for system programming, real-time diagnostics, and unified elopement event logging while providing a foundational hardware footprint for initial facility entry-point deployment.

ARCHITECTS AND ENGINEERS (A&E) SPECIFICATION

- **System Infrastructure:** The contractor shall supply, install, and configure the Accutech 950004-ID BR Startup Kit to act as the primary configuration and initialization interface bridging the peripheral exit network and the central management workstation. The hardware must support bidirectional communication to synchronize active bypass states, tag initialization registries, and real-time controller logs directly with the host computer software.
- **Healthcare Environment Protection:** The data translation assembly shall incorporate a durable, commercial-grade structural design explicitly engineered to sustain continuous clinical exposure, operating reliably across standard high-traffic healthcare IT environments.
- **Access and Control:** The device's physical data interface shall feature automated data direction control paths to allow authorized clinical staff, security personnel, and system administrators to issue network-wide bypass commands, hardware configuration adjustments, and alarm resets from the central software console.
- **Enclosure and Durability:** The interface electronic component assembly shall be protected inside a compact, ruggedized commercial-grade housing optimized for inline placement or clean mounting behind administrative terminal workstations or central distribution centers.
- **System Interoperability:** The interface architecture must feature validated native compatibility for direct connection with Accutech BR series wander management systems, ensuring non-latent signaling, baseline software handshakes, and credential processing across the facility's dedicated security network.

SYSTEM COMPONENTS

The 950004-ID BR Startup Kit incorporates several fundamental integrated sub-modules and physical connection layouts:

- **High-Speed BR Series Core Processing Chipset:** The primary internal multi-layer integrated circuit board dedicated to handling automated initialization algorithms, zone sync pathways, and bidirectional network conversion protocols.
- **Industrial System Interconnect Interface Ports:** A ruggedized, low-resistance mechanical compression interface configured to accept hardwired lines from peripheral controllers and master administration terminals.
- **Dedicated Data Configuration Port Layout:** An integrated, high-durability physical port layout designed for a direct, secure connection to local host workstations, programming dongles, or server expansion slots.
- **Transient Voltage & Protocol Protection Array:** Internal safety circuitry engineered to isolate delicate computing elements from data line surges, grounding faults, and electrostatic discharge (ESD).
- **Vandal-Resistant Infrastructure Case Matrix:** A lightweight, commercial-grade impact-resistant shell providing absolute physical protection for interior circuits within busy administrative deployment spaces.

FEATURES AND BENEFITS

- **Centralized Boundary Awareness:** Consolidates multiple peripheral controller channels down to a single foundation connection on the administration server, greatly simplifying hardware footprints and reducing response times for clinical teams.
- **Seamless Protocol Conversion:** Automatically translates complex electronic security identifiers and elopement codes into standard virtual infrastructure layouts without data packet loss or communication delays.
- **Rapid Deployment Configuration:** Delivers a bundled foundational package engineered to establish initial system operation, tag enrollment, and exit protection without complex custom controller fabrication delays.
- **Diagnostic Status Indicators:** Features integrated LED pathways to provide clear visual feedback on data transmission, upload verification, and power presence, streamlining troubleshooting tasks for facility maintenance teams.
- **Validated Platform Interoperability:** Engineered for native plug-and-play compatibility with Accutech security networks and BR software suites, ensuring a unified approach to facility patient protection.

PRODUCT SPECIFICATION

Manufacturer	Accutech Healthcare Security Solutions
Product Model Name	BR Startup Kit Component Assembly
Part Number / SKU	950004-ID
Component Technology Type	Central System Optimization, Baseline Programming & Network Data Interface Hub

Host Workstation Link	High-Speed Integrated Serial / USB System Communication Interface Loop
Device Interface Port	Dedicated Power Input & Startup Communication Port Layouts
Kit Packaging Contents	Master BR Infrastructure Module, Programming Interfaces, Baseline Reference Software
Input Operating Voltage	12 VDC System Nominal Supply Loop Target
Visual Diagnostic Indicators	Dedicated Feedback Arrays for Power Input and Active Data Transfer Verification
Wander System Compatibility	Accutech ResidentGuard, BR Series, and Integrated System Environments
Chassis Construction	High-Impact, Commercial-Grade Structural Thermoplastic / Composite Shell
Primary Target Environments	Central IT Server Closets, Technical Terminals, Main Administration Desks

COMPLIANCE AND CERTIFICATION

- **FCC Status:** Designed and certified to meet FCC regulations regarding digital device shielding. This guarantees that internal motor microprocessors, switching pathways, and high-speed data translation steps do not introduce or sustain harmful electromagnetic interference across nearby diagnostic clinical devices or patient networks.
- **UL Listing:** Developed and engineered using interior assembly components compliant with UL safety classifications for low-voltage access control locking mechanisms, information technology equipment, and auxiliary healthcare resident safety tools.
- **RoHS Compliance:** Formulated in alignment with environmental protection directives, ensuring that the internal circuit layouts, external terminal components, and housing finishes strictly restrict the use of lead, mercury, polybrominated biphenyls, and other hazardous materials.