



**182-24RB
Paging Display**

182-24RB Paging Display

The 182-24RB paging display features a two line alphanumeric LED display available in either 24" or 48". The 182-24RB receives wireless POCSAG data input from the SPS5. It includes features such as 10 to 40 display characters per line and real time clock. The characters are displayed at a minimum height of 4.75" and can be read at a distance of up to 200 feet. The time from alarm to message reception is typically under two seconds.

Architects' and Engineers' Specifications

The BEC LED paging display part number 182-24RB will receive encode serial data into POCSAG. It shall connect to the SPS5 and receive calls from the console/master station via a wireless connection and shall display full alarm escalation.

Specification

- Dimensions of 24": Length: 28"
- Width: 3"
- Height: 6"
- Dimensions of 48": Length: 52"
- Width: 3"
- Height: 6"
- Weight 24": 8.5 lb
- Weight 48": 15.25 lb
- Power Supply: 120VAC Adapter
- Transmitter Power: 25KHz

Features

- Wireless data input
- 10-40 characters per line
- Accepts 2,000 characters per message
- Display memory of 163,200 bytes

System Components

<u>Model No.</u>	<u>Description</u>
Server 2	Video Display Console
MV400	400 Desk Master
SPS5	Paging Transmitter
MV200	200 Desk Master