




Architects and Engineers Specifications

The wireless RFID locator shall be Systems Technologies part number WNC-125LHB All locators shall be compatible with the WNC-Server2 and MV500 Consoles. The console shall be capable of providing wearer location with a personal pendant transmitter alarm. The alarm notification shall include the resident name and RFID locator name. This information shall be selectable on a WNC-Server2 or MV500 wireless console and display automatically on the associated staff notification devices. The locator detection field shall be within six feet to make the location floor specific in a multi-story building when used with the transmitter and wrist necklace pendant. The location name shall automatically update as the resident walks past each locator when used with passive location pendants. Each wireless pendant type is equipped with "Push for Help" button.

Specifications

- **Dimensions:** 0.87" high, 3.25" wide, 4.68" long
- **Weight:** 8.25 ounces including batteries
- **Panel:** Polycarbonate
- **Batteries:** Four AA Duracell Procell 1500mA

WNC-125LHB

The WNC-125LHB is a wireless surface mount locator that consists of an RFID detector and four user replaceable batteries. The WNC-125LHB is engineered to be installed in a six foot wide hallway. The wireless RFID locator can detect a necklace pendant and wrist pendant. The locators detect a wireless pendant transmitter within approximately six feet. It enables the wearer location to be identifiable by floor, area or room in a multi-story building where locators are installed. When used with the passive location pendants the location name will automatically update as a pendant walks past each locator and can notify staff in the new notification area with the resident name and current location. Each WNC-125LHB has a separate ID that is programmed into a WNC-SERVER2 or MV500 Wireless Emergency Call System. When an alarm is originated from any programmed and enabled pendant transmitter, the pendant ID and RFID locator ID send both the resident name and RFID locator name to the consoles which displays on the staff notification options installed such as Vision Link mobile app, scrolling LED reader boards, email, text messaging, pocket pagers, or other notification devices.

System Components

WNC-Server2	Master Station Console
MV500	MV500 Console
WM-Tester	Required coverage tester for WNC-125LHB
WNC-NP	Water resistant RF/RFID necklace pendant
WNC-WP	Water resistant RF/RFID wrist pendant

Features

- Supervised for operation and battery life
- Includes four 1500mA batteries
- LED transmit indicator
- Surface mount design includes drywall screws
- Detects RFID pendants within 6 feet of locator eye
- Works with passive location pendants