



Architects' and Engineers' Specifications

The Emergency call system shall be equipped with WNC-FP personal transmitters that automatically detect a fall impact and transmit programmed information with an alarm when used with included belt clip. This 900MHz RF/RFID unit shall include a transmit button for push button calling, a red transmit LED indicator that blinks to Show a call being placed and a green LED indicator that blinks when the alarm is cancelled. A one second depression of the transmit button shall result in the alarm signal being transmitted multiple times and the red LED Will flash. unit shall be water resistant and include a plastic necklace chain and battery. It shall have a non-volatile memory and supervised for operation and battery voltage.

Features

- Reliable 900 MHz spread frequency transmission
- Two color LED for easy identification of alarm and reset
- Simple push button calling.
- Automatic fall impact detection when used with holster
- Magnetic "Re-Set" for alarm cancellation
- Alarm signals are transmitted multiple times
- Fully supervised for operation and battery

WNC-FP Fall Alarm Pendant

The WNC-FP is a 900MHz spread spectrum, water resistant RF/RFID mini-transmitter with belt clip attachment, push for help button, magnetic call cancel and dual color LED with alarm in red and reset in green. The fall function requires the included belt clip for attachment to the user's belt or waistband. The fall alarm transmitter will automatically send alarm with the user's name and any programmed location information if the transmitter detects a fall impact. Weighing in at just eight tenths of an ounce, the WNC-FP features a water resistant housing that protects the pendant when worn in the shower, bathtub, or Other environments where the pendant may be submerged. It is not recommended for use by divers or in pools or spas where chlorine and other chemicals may shorten the life expectancy. It features easy single button activation and a raised bump for use at night or by the visually impaired. Calls are magnetically reset with the tool which provides a reset magnet on one end and battery door tool on the other end.

Specification

- Dimensions w/wrist strap: Height: 2.38"
Width: 1.75"
Depth: 1.03"
- Weight: 1 oz
- Battery: 3.0V Lithium CR2450
- Battery Life: 1-2 years (fully supervised)
- Supervisory Transmission: 1 Hour

System Components

<u>Model No.</u>	<u>Description</u>
Server 2	Video Display Console
MV400	Desk Console Receiver
MV200	Desk Console Receiver
WNC-CC	Locator Beacon
WNC-RPH	Repeater/ Locator-High power
WNC-RP	Repeater/ Locator