

DP7500

6,720 RUNNING WATTS


Rugged Steel Design



— Honda GX390 Commercial Engine -



Brushless Industrial Genend



—— LED Display –

Hours, RPMs, voltage, and frequency readings automatically cycle on the display.



Load Bars

Easily verify the load balance on each leg of the generator end.




Warnings -

The LED will flash if any parameter gets outside of normal range. A warning will also be displayed when it is time for an oil change.





with GFCI protection



NEUTRAL BONDED TO FRAME NEUTRE MIS A LA MASSE A LA CARCASSE DU MOTEUR

ENGIN	NE∘
ENGINE BRAND	HONDA
ENGINE MODEL	GX390
ENGINE STARTER	RECOIL/ELECTRIC
ENGINE SPEED	3600 RPM
ENGINE CYLINDERS	SINGLE
DISPLACEMENT/TYPE	389 CC / OHV
FREQUENCY REGULATION ⁽¹⁾	+/- 3%
LOW OIL PROTECTION	STANDARD
RECOMMENDED OIL ⁽²⁾	10W-30
OIL CAPACITY	1.2 QT
FUEL TANK	8 GAL
FUEL GAUGE	ON TANK
FULL LOAD RUN TIME ⁽³⁾	8 HOURS
FUEL CONSUMPTION 100% 75% 50% 25% 0%	GAL/HR 1.00 0.78 0.58 0.44 0.30
BATTERY SIZE ⁽⁴⁾	BCI 20 OR 24HL 300CCA

NOTES: (1) Steady state frequency regulation. (2) The recommended oil is for normal applications. See operator's manual for the recommended oil for your needs. (3) Run time is estimated. (4) Battery not included.

○ OPTIONAL ACCESSORIES ○

TWO-WHEEL DOLLY KIT	WITH FLAT-FREE TIRES
COVER	34.75" x 25" x 24.5"
BATTERY	BCI 20 OR 24HL 300 CCA
MAINTENANCE KIT	16200-003

•—— ELECT	RICAL ———
STARTING WATTS	7,500
RUNNING WATTS	6,720
RUNNING AMPS @ 120 VAC	56
RUNNING AMPS @ 240 VAC	28
VOLTAGE REGULATION	CAPACITOR +/- 5%
MAIN CIRCUIT BREAKER	30 AMP, 240V (GFCI)
BONDED NEUTRAL	YES
120 VOLT RECEPTACLES	(2) NEMA 5-20 20A (GFCI)
120/240 VOLT RECEPTACLES	(1) NEMA L14-30 30A (GFCI)
YOURGEN METER	STANDARD

• GENSET		
MOTOR STARTING (CODE G)	2 HP	
DBA @ 7 METERS	83.7	
TOTAL HARMONIC DISTORTION	< 6%	
LIFTING EYE ⁽¹⁾	STANDARD	
2-WHEEL DOLLY KIT	OPTIONAL	
INSULATION	CLASS H	
PROTECTIVE ROLL FRAME	1.25" DIA. 14 GA. STEEL	
ASSEMBLED IN	USA	
EPA APPROVED	YES	
CARB APPROVED	YES	
CSA APPROVED	NO	
UNIT WARRANTY ⁽²⁾	3 YEARS COMMERCIAL	

NOTES: (1) Lifting eye shipped loose. (2) For more generator warranty, see operator's manual.

SHIPPING	o
SHIPPING DIMENSIONS (LxWxH)	30" x 22" x 24"
SHIP WEIGHT	210 LBS
FREIGHT CLASS	70







39.9"