



VICTORY FIRE & GAS INC.

www.victoryfiregas.com
info@victoryfiregas.com

Michigan Corporate Office
1713 Lewis St
Bay City MI 48706
989.322 0856

Texas
15550 West Hardy
Houston TX 77060
281 405 0175

Illinois
162 N. Brandon Dr.
Glendale Heights IL 60139
312 965 2697

Northern CA
2214 American Ave
Hayward CA 94545
510 861 5311

Pennsylvania
30 Three Tun Rd, Unit C
Malvern PA 19335
267 963 6411

Southern CA
14841 Proctor Ave Unit C
City of Industry CA 91746
626.333 3033

Florida
5182 Le Tourneau Circle
Tampa FL 33610
813 999 4424

Georgia
3968 Shirley Drive
Atlanta GA 30336
770 283 4780


CANADA BC
104-1772 Broadway St.
Port Coquitlam, BC V3C2M8
778-222-6765

CANADA Toronto ON
1104 Fewster Drive Unit 12 & 13
Mississauga ON L4W2V7
416-898-6390

CARBON DIOXIDE 5LB CO2 FIRE EXTINGUISHER

MODEL: C05LB

STANDARD COMPLIED WITH: DOT.ANSI/UL154



FEATURES:

Suitable for Class B and C Fires
Plated Brass Valve with Stainless Steel Handles
Aluminum Cylinder
100% Leak Tested
Production Under ISO9001 Quality System



TECHNICAL SPECIFICATION

Model Number	C05LB
Capacity / lb (/kg)	5(2.27)
Cylinder Diameter / in (/mm)	5.24(133)
Height / in (/mm)	17.13(435)
Width / in (/mm)	8.07(205)
Discharge Time / s	9
Fire Rating	5-B:C
Extinguisher Weight / lb (/kg)	13.29(6.03)
Packing Size(L×W×H) / in (/mm)	7.67×5.7×17.72(195×145×450)
Discharge Range / ft (/m)	4-8(1.2-2.4)
Operation Temperature / F (/C)	-22~120(-30~49)
UL list File Number	EX 27916
Marine Type	/
USCG Approval Number	/

* Transport Classification: Non-Flammable, Non-Toxic Gas.
UN No. 1044 Class 2.2

Valve		024314001
Seal		0714025
Lever		0202148
Rivet		0204029
Carry Handle		0203125
Valve Body		020504042
Bracket		070200005
Safety Gasket		022304009
Safety Disc		0233007
Safety Cap		0212043
O Ring		020601126
Valve Stem Assembly		0220110
Spring		020701010
Tube Holder		020801036
Dip Tube		080402047
Cylinder		050100088
Safety Pin		30420050
Chain		0210001
Connector		0242021
Hose Assembly		080100046