

SHEET 16  
LTPP MONITORED TRAFFIC DATA  
SITE CALIBRATION SUMMARY

\*STATE ASSIGNED ID [ 0521 ]  
\*STATE CODE [ 04 ]  
\*SHRP SECTION ID [ 7079 ]

SITE CALIBRATION INFORMATION

file 800.12.28.12

1. \* DATE OF CALIBRATION (MONTH/DAY/YEAR) [ 06 / 11 / 2003 ]
2. \* TYPE OF EQUIPMENT CALIBRATED ☒ WIM ☐ CLASSIFIER ☐ BOTH
3. \* REASON FOR CALIBRATION  
☒ REGULARLY SCHEDULED SITE VISIT ☐ RESEARCH  
☐ EQUIPMENT REPLACEMENT ☐ TRAINING  
☐ DATA TRIGGERED SYSTEM REVISION ☐ NEW EQUIPMENT INSTALLATION  
☐ OTHER (SPECIFY) \_\_\_\_\_
4. \* SENSORS INSTALLED IN LTPP LANE AT THIS SITE (CHECK ALL THAT APPLY):  
☐ BARE ROUND PIEZO CERAMIC ☐ BARE FLAT PIEZO ☐ BENDING PLATES  
☒ CHANNELIZED ROUND PIEZO ☐ LOAD CELLS ☐ QUARTZ PIEZO  
☐ CHANNELIZED FLAT PIEZO ☒ INDUCTANCE LOOPS ☐ CAPACITANCE PADS  
☐ OTHER (SPECIFY) \_\_\_\_\_
5. EQUIPMENT MANUFACTURER PAT AMERICA.

WIM SYSTEM CALIBRATION SPECIFICS\*\*

- 6.\*\* CALIBRATION TECHNIQUE USED:  
☐ TRAFFIC STREAM -- ☐ STATIC SCALE (Y/N) ☒ TEST TRUCKS  
☐ NUMBER OF TRUCKS COMPARED ☐ 1 NUMBER OF TEST TRUCKS USED

TYPE PER FHWA 13 BIN SYSTEM	PASSES PER TRUCK	
	TRUCK	SUSPENSION
SUSPENSION: 1 - AIR; 2 - LEAF SPRING	1	1
3 - OTHER (DESCRIBE)	2	
	3	

7. SUMMARY CALIBRATION RESULTS (EXPRESSED AS A PERCENT)  
MEAN DIFFERENCE BETWEEN ---  
DYNAMIC AND STATIC GVW 1.9 STANDARD DEVIATION 9.1  
DYNAMIC AND STATIC SINGLE AXLES 0.0 STANDARD DEVIATION 11.3  
DYNAMIC AND STATIC DOUBLE AXLES 8.4 STANDARD DEVIATION 7.8
8. 3 NUMBER OF SPEEDS AT WHICH CALIBRATION WAS PERFORMED
9. DEFINE THE SPEED RANGES USED (MPH) 55, 65, & 75
10. CALIBRATION FACTOR (AT EXPECTED FREE FLOW SPEED) \_\_\_\_\_
- 11.\*\* IS AUTO-CALIBRATION USED AT THIS SITE? (Y/N) N  
IF YES, LIST AND DEFINE AUTO-CALIBRATION VALUE: \_\_\_\_\_

CLASSIFIER TEST SPECIFICS\*\*\*

- 12.\*\*\* METHOD FOR COLLECTING INDEPENDENT VOLUME MEASUREMENT BY VEHICLE CLASS:  
☐ VIDEO ☒ MANUAL ☐ PARALLEL CLASSIFIERS

SEP 12 2003

*[Signature]*