

SHEET 16
LTPP MONITORED TRAFFIC DATA
SITE CALIBRATION SUMMARY

*STATE ASSIGNED ID [0521]
*STATE CODE [04]
*SHRP SECTION ID [7079]

SITE CALIBRATION INFORMATION

file 800.12.28.12

1. * DATE OF CALIBRATION (MONTH/DAY/YEAR) [06 / 11 / 2003]
2. * TYPE OF EQUIPMENT CALIBRATED ☒ WIM ☐ CLASSIFIER ☐ BOTH
3. * REASON FOR CALIBRATION
☒ REGULARLY SCHEDULED SITE VISIT ☐ RESEARCH
☐ EQUIPMENT REPLACEMENT ☐ TRAINING
☐ DATA TRIGGERED SYSTEM REVISION ☐ NEW EQUIPMENT INSTALLATION
☐ OTHER (SPECIFY) _____
4. * SENSORS INSTALLED IN LTPP LANE AT THIS SITE (CHECK ALL THAT APPLY):
☐ BARE ROUND PIEZO CERAMIC ☐ BARE FLAT PIEZO ☐ BENDING PLATES
☒ CHANNELIZED ROUND PIEZO ☐ LOAD CELLS ☐ QUARTZ PIEZO
☐ CHANNELIZED FLAT PIEZO ☒ INDUCTANCE LOOPS ☐ CAPACITANCE PADS
☐ OTHER (SPECIFY) _____
5. EQUIPMENT MANUFACTURER PAT AMERICA.

WIM SYSTEM CALIBRATION SPECIFICS**

- 6.** CALIBRATION TECHNIQUE USED:
☐ TRAFFIC STREAM -- ☐ STATIC SCALE (Y/N) ☒ TEST TRUCKS
☐ NUMBER OF TRUCKS COMPARED ☐ 1 NUMBER OF TEST TRUCKS USED

TYPE PER FHWA 13 BIN SYSTEM SUSPENSION: 1 - AIR; 2 - LEAF SPRING 3 - OTHER (DESCRIBE)	PASSES PER TRUCK	
	TRUCK	TYPE SUSPENSION
	1	9 1
	2	
	3	

7. SUMMARY CALIBRATION RESULTS (EXPRESSED AS A PERCENT)
MEAN DIFFERENCE BETWEEN ---
DYNAMIC AND STATIC GVW 1.9 STANDARD DEVIATION 9.1
DYNAMIC AND STATIC SINGLE AXLES 0.0 STANDARD DEVIATION 11.3
DYNAMIC AND STATIC DOUBLE AXLES 8.4 STANDARD DEVIATION 7.8
8. 3 NUMBER OF SPEEDS AT WHICH CALIBRATION WAS PERFORMED
9. DEFINE THE SPEED RANGES USED (MPH) 55, 65, & 75
10. CALIBRATION FACTOR (AT EXPECTED FREE FLOW SPEED) _____
- 11.** IS AUTO-CALIBRATION USED AT THIS SITE? (Y/N) N
IF YES, LIST AND DEFINE AUTO-CALIBRATION VALUE: _____

CLASSIFIER TEST SPECIFICS***

- 12.*** METHOD FOR COLLECTING INDEPENDENT VOLUME MEASUREMENT BY VEHICLE CLASS:
☐ VIDEO ☒ MANUAL ☐ PARALLEL CLASSIFIERS

SEP 12 2003

[Signature]