

Traffic Sheet 16 LTTP MONITORED TRAFFIC DATA SITE CALIBRATION SUMMARY	STATE CODE:	05
	SPS WIM ID:	050200
	DATE (mm/dd/yyyy)	7/10/2013

SITE CALIBRATION INFORMATION

1. DATE OF CALIBRATION {mm/dd/yy} 7/10/13
2. TYPE OF EQUIPMENT CALIBRATED: Both
3. REASON FOR CALIBRATION: LTTP Validation
4. SENSORS INSTALLED IN LTTP LANE AT THIS SITE (Select all that apply):

a. <u>Inductance Loops</u>	c. <u></u>
b. <u>Bending Plates</u>	d. <u></u>
5. EQUIPMENT MANUFACTURER: IRD iSINC

WIM SYSTEM CALIBRATION SPECIFICS

6. CALIBRATION TECHNIQUE USED: Test Trucks

Number of Trucks Compared:	<u></u>
Number of Test Trucks Used:	<u>2</u>
Passes Per Truck:	<u>20</u>

	Type	Drive Suspension	Trailer Suspension
Truck 1:	<u>9</u>	<u>steel spring</u>	<u>air</u>
Truck 2:	<u>9</u>	<u>steel spring</u>	<u>air</u>
Truck 3:	<u></u>	<u></u>	<u></u>

7. SUMMARY CALIBRATION RESULTS (expressed as a %):

Mean Difference Between -

Dynamic and Static GVW:	<u>2.4%</u>	Standard Deviation:	<u>2.4%</u>
Dynamic and Static Single Axle:	<u>4.7%</u>	Standard Deviation:	<u>3.6%</u>
Dynamic and Static Double Axles:	<u>1.6%</u>	Standard Deviation:	<u>2.8%</u>

8. NUMBER OF SPEEDS AT WHICH CALIBRATION WAS PERFORMED: 3

9. DEFINE SPEED RANGES IN MPH:

	Low		High	Runs
a. <u>Low</u>	-	<u>54.0</u>	to <u>57.3</u>	<u>16</u>
b. <u>Medium</u>	-	<u>57.4</u>	to <u>60.8</u>	<u>13</u>
c. <u>High</u>	-	<u>60.9</u>	to <u>64.0</u>	<u>11</u>
d. <u></u>	-	<u></u>	to <u></u>	<u></u>
e. <u></u>	-	<u></u>	to <u></u>	<u></u>

Traffic Sheet 16 LTPP MONITORED TRAFFIC DATA SITE CALIBRATION SUMMARY	STATE CODE:	05
	SPS WIM ID:	050200
	DATE (mm/dd/yyyy)	7/10/2013

10. CALIBRATION FACTOR (AT EXPECTED FREE FLOW SPEED) 2912 | 2981

11. IS AUTO- CALIBRATION USED AT THIS SITE? No

If yes , define auto-calibration value(s):

CLASSIFIER TEST SPECIFICS

12. METHOD FOR COLLECTING INDEPENDENT VOLUME MEASUREMENT BY VEHICLE CLASS:

Manual

13. METHOD TO DETERMINE LENGTH OF COUNT: Number of Trucks

14. MEAN DIFFERENCE IN VOLUMES BY VEHICLES CLASSIFICATION:

FHWA Class 9:		FHWA Class		-	
FHWA Class 8:		FHWA Class		-	
		FHWA Class		-	
		FHWA Class		-	

Percent of "Unclassified" Vehicles: 1.8%

Validation Test Truck Run Set - Pre

Person Leading Calibration Effort:	<u>Dean Wolf</u>		
Contact Information:	Phone:	<u>717-975-3550</u>	
	E-mail:	<u>dwolf@ara.com</u>	

Traffic Sheet 16 LTPP MONITORED TRAFFIC DATA SITE CALIBRATION SUMMARY	STATE CODE:	05
	SPS WIM ID:	050200
	DATE (mm/dd/yyyy)	7/11/2013

SITE CALIBRATION INFORMATION

1. DATE OF CALIBRATION {mm/dd/yy} 7/11/13
2. TYPE OF EQUIPMENT CALIBRATED: Both
3. REASON FOR CALIBRATION: LTPP Validation
4. SENSORS INSTALLED IN LTPP LANE AT THIS SITE (Select all that apply):

a. <u>Inductance Loops</u>	c. <u></u>
b. <u>Bending Plates</u>	d. <u></u>
5. EQUIPMENT MANUFACTURER: IRD iSINC

WIM SYSTEM CALIBRATION SPECIFICS

6. CALIBRATION TECHNIQUE USED: Test Trucks

Number of Trucks Compared:	<u></u>
Number of Test Trucks Used:	<u>2</u>
Passes Per Truck:	<u>20</u>

	Type	Drive Suspension	Trailer Suspension
Truck 1:	<u>9</u>	<u>steel spring</u>	<u>air</u>
Truck 2:	<u>9</u>	<u>steel spring</u>	<u>air</u>
Truck 3:	<u></u>	<u></u>	<u></u>

7. SUMMARY CALIBRATION RESULTS (expressed as a %):

Mean Difference Between -

Dynamic and Static GVW:	<u>-0.1%</u>	Standard Deviation:	<u>2.0%</u>
Dynamic and Static Single Axle:	<u>1.3%</u>	Standard Deviation:	<u>3.5%</u>
Dynamic and Static Double Axles:	<u>0.8%</u>	Standard Deviation:	<u>2.7%</u>

8. NUMBER OF SPEEDS AT WHICH CALIBRATION WAS PERFORMED: 3

9. DEFINE SPEED RANGES IN MPH:

		Low		High	Runs
a.	<u>Low</u>	<u>54.0</u>	to	<u>57.7</u>	<u>12</u>
b.	<u>Medium</u>	<u>57.8</u>	to	<u>61.4</u>	<u>14</u>
c.	<u>High</u>	<u>61.5</u>	to	<u>65.0</u>	<u>14</u>
d.	<u></u>	<u></u>	to	<u></u>	<u></u>
e.	<u></u>	<u></u>	to	<u></u>	<u></u>

Traffic Sheet 16 LTPP MONITORED TRAFFIC DATA SITE CALIBRATION SUMMARY	STATE CODE:	05
	SPS WIM ID:	050200
	DATE (mm/dd/yyyy)	7/11/2013

10. CALIBRATION FACTOR (AT EXPECTED FREE FLOW SPEED) 2884 2953

11. IS AUTO- CALIBRATION USED AT THIS SITE? No

If yes , define auto-calibration value(s):

CLASSIFIER TEST SPECIFICS

12. METHOD FOR COLLECTING INDEPENDENT VOLUME MEASUREMENT BY VEHICLE CLASS:

Manual

13. METHOD TO DETERMINE LENGTH OF COUNT: Number of Trucks

14. MEAN DIFFERENCE IN VOLUMES BY VEHICLES CLASSIFICATION:

FHWA Class 9:		FHWA Class		-	
FHWA Class 8:		FHWA Class		-	
		FHWA Class		-	
		FHWA Class		-	

Percent of "Unclassified" Vehicles: 0.0%

Validation Test Truck Run Set - Post

Person Leading Calibration Effort:	Dean Wolf		
Contact Information:	Phone:	717-975-3550	
	E-mail:	dwolf@ara.com	